

FA14015B

MOLDED CASE CIRCUIT BREAKER 480Y/277V 15A

Product availability : Stock - Normally stocked in distribution facility



Price* : 302.00 USD



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip unit technology	Thermal-magnetic
Breaking capacity code	A

Complementary

Line Rated Current	15 A
Poles description	1P
Breaking capacity	10 kA at 125 V DC 18 kA at 480Y/277 V AC 25 kA at 120/240 V AC
System Voltage	480Y/277 V AC
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 14...AWG 4 (copper) 1 cable(s) AWG 12...AWG 4 (aluminium) 1 cable(s)
Terminal identifier	AL50FA
Magnetic hold current	275 A
Magnetic tripping current	600 A

Environment

Product certifications	UL listed CSA
------------------------	------------------

Ordering and shipping details

Category	01005 - FA 480V BREAKER & SWITCH
----------	----------------------------------

Discount Schedule	DE2
GTIN	00785901648826
Nbr. of units in pkg.	1
Package weight(Lbs)	2.4399999999999999
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------