

# FA14015C

## MOLDED CASE CIRCUIT BREAKER 480Y/277V 15A

Product availability : Stock - Normally stocked in distribution facility



Price\* : 302.00 USD



### Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip unit technology	Thermal-magnetic
Breaking capacity code	A

### Complementary

Line Rated Current	15 A
Poles description	1P
Breaking capacity	10 kA at 125 V DC 18 kA at 480Y/277 V AC 25 kA at 120/240 V AC
System Voltage	480Y/277 V AC
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 14...AWG 4 (copper) 1 cable(s) AWG 12...AWG 4 (aluminium) 1 cable(s)
Terminal identifier	AL50FA
Magnetic hold current	275 A
Magnetic tripping current	600 A

### Environment

Product certifications	CSA UL listed
------------------------	------------------

### Ordering and shipping details

Category	01005 - FA 480V BREAKER & SWITCH
----------	----------------------------------

Discount Schedule	DE2
GTIN	00785901648833
Nbr. of units in pkg.	1
Package weight(Lbs)	2.48
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------