

LAP36400MB

3P 600V 400A MOULDED CASE CIRCUIT BREAKER

Product availability : Stock - Normally stocked in distribution facility



Price* : 4619.00 USD



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip unit technology	Magnetic
Breaking capacity code	A
Accessory / separate part type	Handle

Complementary

Line Rated Current	400 A
Poles description	3P
Breaking capacity	42 kA at 240 V AC 30 kA at 480 V AC 22 kA at 600 V AC 10 kA at 125 V DC 10 kA at 250 V DC
System Voltage	600 V AC
Mounting mode	Unit mount
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 1...600 kcmil (aluminium/copper) 1 cable(s) AWG 1...250 kcmil (aluminium/copper) 2 cable(s)
Terminal identifier	AL400LA
Magnetic hold current	2000 A
Magnetic tripping current	4000 A
Operator profile	Short lever
Wiring configuration	3-wire

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Environment

Product certifications	UL listed CCC IEC CSA
------------------------	--------------------------------

Ordering and shipping details

Category	00935 - LAL/LHL BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901650386
Nbr. of units in pkg.	1
Package weight(Lbs)	15.800000000000001
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------