

7500CD

DENTAL LAB STEAM CLEANER

PRODUCT SPECIFICATIONS

THE POWER OF STEAM

The 7500CD produces 70 PSI of steam pressure and reaches temperatures up to 221° F at the tip. It's ideally suited for use in dental labs, jewelry stores and workrooms for cleaning away left over wax, plaster waste and other debris, and for polishing the final product.

WHY CLEAN WITH STEAM?

Steam deodorizes and sanitizes with heat and moisture and since the only ingredient required for the 7500CD is water, cleaning has never been safer, healthier or more environmentally friendly.

FEATURES

- Reset thermostat
- Water level indicator window
- 4 safety systems
- 30-40 minute heat up time
- Pressure gauge
- Up to 8 hours of continuous steam
- Incoloy heating elements
- Blow down valve with fittings

ELECTRICAL	120V
WATER CAPACITY	2.37 US gallons - 9L
OPERATING PRESSURE	Up to 70 PSI - 4.8 bar
STEAM TEMPERATURE	221°F - 105°C
ELEMENTS	2 - 1,200W each (1 spare)
POWER CONSUMPTION	10 amps
TANK CONSTRUCTION	Stainless steel
LOW WATER INDICATOR	Standard
STEAM CONNECTOR TYPE	Quick-release
NET WEIGHT	33 lb - 15 kg
SHIPPING WEIGHT	37 lb - 16.8 kg
PRODUCT DIMENSIONS	12.25" x 14.25" x 20.5"
SHIPPING DIMENSIONS	16" x 14.75" x 24.25"
COUNTRY OF ORIGIN	Italy
ELECTRICAL APPROVAL	cETLus
WARRANTY	Limited 1 year, Lifetime Tank

