



H0125 ALUMINIUM RAMP

4000KG CAPACITY/PAIR (2000KG/PC)

INSTRUCTION MANUAL

These loading ramps are intended for use in loading vehicles and machinery with rubber wheels, tyres or tracks on or off low rises such as shipping containers and small steps.

MAXIMUM HEIGHT LIMIT TO GROUND LEVEL : 200mm
MAXIMUM LOAD evenly distributed: 4000KG/pair. (2000KG/PC)

1. WARNING

- 1.1 Never exceed the rated capacity of your ramp.
- 1.2 Never exceed the capacity of a loading surface.
- 1.3 Use caution at all times when loading and unloading.
- 1.4 Only load and unload onto a stable, level surface.
- 1.5 Never stand in the path of equipment or vehicle. Keep bystanders and children away.
- 1.6 Do not leave attached ramps unattended.
- 1.7 Do not step between rungs.
- 1.8 Ramp surfaces will have less traction when wet. Use caution.
- 1.9 The ramp is not a toy. Do not use it as a jump, scaffold, bridge, ladder or anything other than its designed purpose.
- 1.10 Suitable for rubber tyres, wheels or tracks only. Not to be used with steel tracks.

2. MAINTENANCE

- 2.1 It is the user's responsibility to check the loading ramp and components before each and every use.
If the ramp is damaged, it should NOT be used.
- 2.2 Maintain the ramp by regular cleaning.
- 2.3 Take care when lifting heavy objects.