

# Elite Cables

## Product Part Number

- TSP2304S03XX

## Product Description

- F/UTP, 23AWG solid bare copper, CAT.6A, CMP
- With cross filler
- Overall metal foil screen with drain wire

## Product Features

- High performance of transmission.
- High quality of safety property.
- Sweep frequency up to 650 MHz


## Application

- Structure cabling for horizontal and building backbone cable.
- Transmission of digital and analogue for data, video and audio applications.
- Overall metal shielded providing good protection from EMI noise.
- IEEE 802.3an 10GBASE-T and legacy speeds.
- CDDI / ATM / Token Ring
- IEEE 802.3af (PoE) / IEEE 802.3at (PoE+) / IEEE 802.3bt (PoE++)

## Applicable Standard

- Electrical Transmission
  - ANSI/TIA-568-C.2 (2009)
  - ISO/IEC 11801 (Edition 2.2)
  - IEC 61156-5 (Edition 2.0)
- Flame Test
  - NFPA 262 (CMP)
- Material and Construction
  - UL 444
  - UL 444 LP-Rating 0.5A&0.6A
  - CSA 22.2 NO.214
- EU Directive 2011/65/EC (RoHS2)
- EU 2015/863 (RoHS 3)
- EU Directive 2006/95/EC (LVD)
- CE compliance date: 2010.01.01

## Sectional Drawing



# Elite Cables

## Material and Construction

Conductor	Material	23AWG solid bare copper	
Insulation	Material	Fluorinated Ethylene Propylene (FEP)	
	Color code & diameter	Blue & white/blue Stripe	1.10 ± 0.02 mm
		Orange & white/orange stripe	1.06 ± 0.02 mm
		Green & white/green stripe	1.09 ± 0.02 mm
	Brown & white/brown stripe	1.06 ± 0.02 mm	
Twisted	Description	Left hand direction	
Filler	Material	Fluorinated Ethylene Propylene (FEP)	
Assembly	Description	Left hand direction	
Shield	Material	Mylar tape	
Drain wire	Material	24AWG solid tinned copper	
Shield	Material	Al Mylar tape	
	Description	100 % coverage and mylar side facing out	
Jacket	Material	Low smoke flame retardant polyvinyl chloride (LSFRPVC)	
	Diameter	7.00 ± 0.2 mm	
	Thickness	0.45 ± 0.05 mm	
	Color	Per customer's request	
Marking	ELITE 10GS CAT 6A --- E142890 FTP 4PR 23AWG 90°C C(UL)US CMP-LP (0.6A) --- ETL VERIFIED TO TIA-568-C.2 CAT 6A mmyy <sup>1</sup> RoHS COMPLIANT XXXXFT		
	Note 1: mmyy is date code.		

## Usage & Environmental Condition

Temperature range	Storage & shipping	-20°C to 75°C
	Installation	0°C to 60°C
	Operation	-20°C to 60°C
Minimum bending radius	≥ 4 times of overall diameter	
Maximum pulling tension	≤ 110 N	

# Elite Cables

## Physical & Electrical Characteristics (at 20°C)

Temperature	90°C
Spark test	2.5 KV DC
AC leakage current through overall jacket	≤ 10mA (1.5KV AC)
Cable cold bend	-20°C for 4 hr
Conductor DC resistance	≤ 9.38 Ω/100m
Resistance unbalance	≤ 5%
Dielectric strength	1.5 KV ac for 2 s
Insulation resistance	≥ 5000 MΩ · km
Mutual capacitance	≤ 5.6 nF/100m
Capacitance unbalance pair-to-ground	≤ 330 pF/100m

## Transmission Performance (at 20°C)

Frequency (MHz)	IL	NEXT	PS. NEXT	ACR	PS. ACR	ACRF	PS. ACRF	RL	Propagation Delay	Delay Skew
	Max. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Max. ns/100m	Max. ns/100m
1	2.08	75.30	73.30	73.22	71.22	71.80	68.80	20.00	570.00	45.00
4	3.80	66.27	64.27	62.47	60.47	59.76	56.76	23.01	552.00	
8	5.31	61.75	59.75	56.44	54.44	53.74	50.74	24.52	546.73	
10	5.93	60.30	58.30	54.37	52.37	51.80	48.80	25.00	545.38	
16	7.49	57.24	55.24	49.75	47.75	47.72	44.72	25.00	543.00	
20	8.38	55.78	53.78	47.41	45.41	45.78	42.78	25.00	542.05	
25	9.38	54.33	52.33	44.95	42.95	43.84	40.84	24.32	541.20	
31.25	10.50	52.88	50.88	42.37	40.37	41.90	38.90	23.64	540.44	
62.5	14.99	48.36	46.36	33.37	31.37	35.88	32.88	21.54	538.55	
100	19.14	45.30	43.30	26.17	24.17	31.80	28.80	20.11	537.60	
150	23.68	42.66	40.66	18.98	16.98	28.28	25.28	18.87	536.94	
200	27.58	40.78	38.78	13.21	11.21	25.78	22.78	18.00	536.55	
250	31.07	39.33	37.33	8.26	6.26	23.84	20.84	17.32	536.28	
300	34.27	38.14	36.14	3.88	1.88	22.26	19.26	16.77	536.08	
350	37.25	37.14	35.14	N.A.	N.A.	20.92	17.92	16.30	535.92	
400	40.05	36.27	34.27	N.A.	N.A.	19.76	16.76	15.89	535.80	
450	42.71	35.50	33.50	N.A.	N.A.	18.74	15.74	15.53	535.70	
500	45.26	34.82	32.82	N.A.	N.A.	17.82	14.82	15.21	535.61	
550	47.70	34.19	32.19	N.A.	N.A.	16.99	13.99	14.92	535.54	
600	50.05	33.63	31.63	N.A.	N.A.	16.24	13.24	14.66	535.47	
650	52.33	33.11	31.11	N.A.	N.A.	15.54	12.54	14.42	535.41	

Values above 500MHz are for information only.