

Elite Cables

Product Part Number

- TUR2304S03XX

Product Description

- U/UTP, 23AWG solid bare copper, CAT.6A, CMR
- With cross filler
- With rip cord

Product Features

- High performance of single cable transmission.
- Zigzag jacket design provides excellent performance of six around one bundle transmission.
- Round and smooth jacket without twisted stripe.
- High quality of safety property.
- Sweep frequency up to 650 MHz


Application

- Structure cabling for horizontal and building backbone cable.
- Transmission of digital and analogue for data, video and audio applications.
- IEEE 802.3an 10GBASE-T and legacy speeds.
- CDDI / ATM / Token Ring
- IEEE 802.3af (PoE) / IEEE 802.3at (PoE+)

Applicable Standard

- Electrical Transmission
 - ANSI/TIA-568-C.2 (2009)
 - ISO/IEC 11801 (Edition 2.2)
 - IEC 61156-5 (Edition 2.0)
- Flame Test
 - UL 1666 (CMR)
- Material and Construction
 - UL 444
 - CSA 22.2 NO.214
- EU Directive 2011/65/EC (RoHS2)
- EU Directive 2006/95/EC (LVD)
- CE compliance date: 2010.01.01

Sectional Drawing



Establish Date	2009.08.19	Edition	1.3	Revised Date	2020.01.20
----------------	------------	---------	-----	--------------	------------

Infinity Cable Products
641 East Walnut St.
Carson, CA 90746
310-327-7678

infinity-cable-products.com

Elite Cables

Material and Construction

Conductor	Material	23AWG solid bare copper	
Insulation	Material	Polyolefin (PO)	
	Color code & diameter	Blue & white	1.19 ± 0.02 mm
		Orange & white	1.10 ± 0.02 mm
		Green & white	1.17 ± 0.02 mm
Brown & white		1.08 ± 0.02 mm	
Twisted	Description	Left hand direction	
Filler	Material	Polyolefin (PO)	
Assembly	Description	Left hand direction	
Rip cord	Material	Polyester multi-yarn	
Jacket	Material	Flame retardant polyvinyl chloride (FRPVC)	
	Diameter	8.3 ± 0.2 mm	
	Thickness	1.10 ± 0.10 mm	
	Color	Per customer`s request	
Marking	<p>ELITE 10GS CAT 6A --- E142890 UTP 4PR 23AWG C(UL)US CMR --- ETL VERIFIED TO TIA-568-C.2 CAT 6A mmyy¹ RoHS COMPLIANT XXXXFT</p> <p>Note 1: mmyy is date code.</p>		

Usage & Environmental Condition

Temperature range	Storage & shipping	-20°C to 75°C
	Installation	0°C to 60°C
	Operation	-20°C to 60°C
Minimum bending radius	≥ 4 times of overall diameter	
Maximum pulling tension	≤ 110 N	

Elite Cables

Physical & Electrical Characteristics (at 20°C)

Temperature & voltage rating	75°C / 300V
Spark test	2.5 KV DC
AC leakage current through overall jacket	≤ 10mA (1.5KV AC)
Cable cold bend	-20°C for 4 hr
Conductor DC resistance	≤ 9.38 Ω/100m
Resistance unbalance	≤ 5%
Dielectric strength	1.5 KV ac for 2 s
Insulation resistance	≥ 5000 MΩ · m
Mutual capacitance	≤ 5.6 nF/100m
Capacitance unbalance pair-to-ground	≤ 330 pF/100m
Nominal Velocity of Propagation	66%
Characteristic Impedance	4~250 103±20Ω
	250~500 103±25Ω
	500~650 103±35Ω

Transmission Performance (at 20°C)

Frequency (MHz)	IL	NEXT	PS. NEXT	ACR	PS. ACR	ACRF	PS. ACRF	RL	Propagation Delay	Delay Skew	PS. ANEXT	PS. AACRF
	Max. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Max. ns/100m	Max. ns/100m	Min. dB/100m	Min. dB/100m
1	2.08	78.30	76.30	76.22	74.22	71.80	68.80	20.00	570.00	45.00	67.00	67.00
4	3.80	69.27	67.27	65.47	63.47	59.76	56.76	23.01	552.00		67.00	66.16
8	5.31	64.75	62.75	59.44	57.44	53.74	50.74	24.52	546.73		67.00	60.14
10	5.93	63.30	61.30	57.37	55.37	51.80	48.80	25.00	545.38		67.00	58.20
16	7.49	60.24	58.24	52.75	50.75	47.72	44.72	25.00	543.00		67.00	54.12
20	8.38	58.78	56.78	50.41	48.41	45.78	42.78	25.00	542.05		67.00	52.18
25	9.38	57.33	55.33	47.95	45.95	43.84	40.84	24.32	541.20		67.00	50.24
31.25	10.50	55.88	53.88	45.37	43.37	41.90	38.90	23.64	540.44		67.00	48.30
62.5	14.99	51.36	49.36	36.37	34.37	35.88	32.88	21.54	538.55		65.56	42.28
100	19.14	48.30	46.30	29.17	27.17	31.80	28.80	20.11	537.60		62.50	38.20
150	23.68	45.66	43.66	21.98	19.98	28.28	25.28	18.87	536.94		59.86	34.68
200	27.58	43.78	41.78	16.21	14.21	25.78	22.78	18.00	536.55		57.98	32.18
250	31.07	42.33	40.33	11.26	9.26	23.84	20.84	17.32	536.28		56.53	30.24
300	34.27	41.14	39.14	6.88	4.88	22.26	19.26	16.77	536.08		55.34	28.66
350	37.25	40.14	38.14	2.89	0.89	20.92	17.92	16.30	535.92		54.34	27.32
400	40.05	39.27	37.27	N.A.	N.A.	19.76	16.76	15.89	535.80		53.47	26.16
450	42.71	38.50	36.50	N.A.	N.A.	18.74	15.74	15.53	535.70	52.70	25.14	
500	45.26	37.82	35.82	N.A.	N.A.	17.82	14.82	15.21	535.61	52.02	24.22	
550	47.70	37.19	35.19	N.A.	N.A.	16.99	13.99	14.92	535.54	51.39	23.39	
600	50.05	36.63	34.63	N.A.	N.A.	16.24	13.24	14.66	535.47	50.83	22.64	
650	52.33	36.11	34.11	N.A.	N.A.	15.54	12.54	14.42	535.41	50.31	21.94	

Values above 500MHz are for information only.