



Product Fiche

| | |
|--|------------------|
| Supplier name | Arada |
| Product Code | HOLGAS-M-LOG-LPG |
| Energy Efficiency Class | - |
| Energy Efficiency Index | 79.9 |
| Direct Heat Output | 4.5 kW |
| Nominal Heat Output: High | 4.5 kW |
| Nominal Heat Output: Low | - |
| Indirect Heating Functionality | N/A |
| Indirect Heat Output | N/A |
| Useful Energy Efficiency Net CV : High | - |

Useful Energy Efficiency Net CV : Low -

Heat Output Control Electronic room temperature control plus

Permanent Pilot Power kW N/A

Space Heating Emissions NOx (GCV) -

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations. The installer must be Gas Safe Registered. Appliance will become very hot during use.

Features

| | |
|--|--------------|
| Gas fuel type | LPG |
| Flue type | Conventional |
| Burner Injector Type | JET 120 |
| Stove body type | Freestanding |
| Ecodesign Ready | - |
| Suitable for smoke control areas | N/A |
| Suitable for direct air connection | N/A |
| Suitable for non-combustible 12mm hearth | Yes |
| Max hearth temperature | N/A |

Dimensions

| | |
|---------------------------------------|--------|
| Width | 485 mm |
| Height | 637 mm |
| Depth | 333 mm |
| Flue Diameter | 127 mm |
| Depth from back to centre of top flue | 105 mm |

Performance – Gas

| | |
|----------------------|------------------|
| Gas Efficiency Class | 1 |
| Gas Type | G31 @ 37/29 Mbar |
| Gas Type Efficiency | I3P |
| Nominal Output | 4.5 kW |

Minimum distance to combustibles

| To Rear | To Side | Above |
|---------|---------|--------|
| 300 mm | 300 mm | 300 mm |



Product Fiche

| | |
|--|-----------------|
| Supplier name | Arada |
| Product Code | HOLGAS-M-LOG-NG |
| Energy Efficiency Class | C |
| Energy Efficiency Index | 83.5 |
| Direct Heat Output | 5 kW |
| Nominal Heat Output: High | 5 kW |
| Nominal Heat Output: Low | - |
| Indirect Heating Functionality | N/A |
| Indirect Heat Output | N/A |
| Useful Energy Efficiency Net CV : High | - |

Useful Energy Efficiency Net CV : Low -

Heat Output Control Electronic room temperature control plus day timer

Permanent Pilot Power kW N/A

Space Heating Emissions NOx (GCV) -

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations. The installer must be Gas Safe Registered. Appliance will become very hot during use.

Features

Gas fuel type Natural Gas

Flue type Conventional

Stove body type Freestanding

Ecodesign Ready -

Suitable for smoke control areas N/A

Suitable for direct air connection N/A

Suitable for non-combustible 12mm hearth Yes

Max hearth temperature N/A

Dimensions

| | |
|---------------------------------------|--------|
| Width | 485 mm |
| Height | 637 mm |
| Depth | 333 mm |
| Flue Diameter | 127 mm |
| Depth from back to centre of top flue | 105 mm |

Performance – Gas

| | |
|----------------------|--------------|
| Gas Efficiency Class | 1 |
| Gas Type | G20 @ 20Mbar |
| Gas Type Efficiency | I2H |
| Nominal Output | 5 kW |

Minimum distance to combustibles

| To Rear | To Side | Above |
|---------|---------|--------|
| 300 mm | 300 mm | 300 mm |