

SLS33DZ Double zone service temperature wine cellar Service range







Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.

This equipment is designed to be used in an ambient temperature between 16 - 32°C.

This appliance is intended to be used exclusively for the storage of wine.

Alcohol abuse is dangerous for health, please consume in moderation.

*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 4 shelves. Adding shelves reduce considerably the total capacity. **Thanks to the Vinotag® application, benefit from a digital register of your

**Thanks to the Vinotag® application, benefit from a digital register of your wine cellar and be alerted of the peak dates of your wines. In partnership with Vivino, scan your bottle to access its pre-filled wine sheet.

- **+** Capacity: 33 bottles*:
 - upper part: 15 bottles
 - lower part: 18 bottles
- 🕂 Vinotag compatible** 🚺
- Free standing installation
- Design: black
- Cooling system: compressor
- Type of cold: static frost
- Adjustable temperature ranges of use:
 upper part: 12° 18° C
 - lower part: 5° 14° C
- + Electronic regulation
- Thermometer with blue digital display
- White LED lights with switch button
- Humidity control: natural (hygrodynamy concept)
- 1 glass door, anti-UV treated, 2-layers tempered glass
 - Modern and compact, SLS33DZ wine cellar is one of La Sommelière's best-sellers. Protected by a tempered glass door, anti-UV treated, your bottles are visible and sublimated thanks to LED interior lighting.
 - Bring your wines to tasting temperature to take full advantage of all their aromas. Thanks to its 2 temperature zones with independent adjustment, you can bring several types of wine to the tasting temperature in the same cellar.
 - **Digital exterior control panel** for more intuitive use and to avoid unwanted temperature movements inside the cellar (vs interior adjustment).
 - **Removable interior** (shelf and lower wine cellar support) in natural wood (beech) to suit your needs. The **lower cellar support** allows you to elegantly store different types of bottles.



SLS33DZ Double zone service temperature wine cellar Service range



> EQUIPMENTS INCLUDED

- 4 fixed wooden shelves (beech)
- 1 wooden bottom cellar support
- 2 adjustable feet (height 1.2 cm)
- Anti-vibration system

> TECHNICAL CHARACTERISTICS

- Energy class: G
- Annual electrical consumption: 136 kWh
- Climatic class: N
- Noise level: 43 dB
- Voltage: 220-240 V
- Power input: 85 W
- Category: 2 Wine cellar
- Type of gas: R600a

> SAFETY

Child lock: locks the control panel

> VINOTAG® APPLICATION

Free wine cellar management application. Access a virtual representation of your wine cellar and a detailed inventory of its contents.

> LOGISTIC DATAS

Gross dimensions (WxDxH cm)		: 53,5 x 46,5 x 88
Net dimensions (WxDxH cm)		: 49,5 x 43 x 84,8
Gross weight (kg)		: 27.70
Net weight (kg)		: 25.40
Full truck (pcs)		: 0
Container (pcs)	20'	: 106
	40'	: 218
	40' HC	: 327
Gencod		3541362009258

> COMPATIBLE ACCESSORIES

Only available in spare parts

Non-contractual pictures Last update: 10/11/2022