

DATA SHEET SWISSCAVE WLB-160F

Technical Data

Exterior	
Casing	Black coated steel
Door glazing	Fully glazed UV-resistant, gas-fil- led, with low energy panes equip- ped glass door (double glazed)
Door frame	Filigree edging made of black anodised, brushed aluminium
Door handle	Anodised, brushed aluminium (rectangular) (optionally available)
Door lock	Yes
Door hinge	Right
Door hinge convertible as option (right to left)	Yes
Product dimensions without door handle (H/W/D)	820 x 595 x 595 mm
Packaging dimensions (H/W/D)	865 x 650 x 655 mm
Interior	
Temperature zones	1
Lighting	all around illumination white, blue, amber (adjustable)
Lighting on/off switch	Yes
Number of shelves total	5
Number of display shelves (for perfect wine presentation)	0 (other shelf types)
Number of bottle levels max.	7
Shelf material	Beech wood
Telescopic shelves on extendable steel ball bearings	Full extension shelves (80%)
Inside casing	Black PUR
Scope of functions	
Optimal usage	Tempering and storing
User interface	Tempering and storing 2 digital displays (set and actual temp.)
	2 digital displays (set and actual
User interface Active carbon filters (ensuring	2 digital displays (set and actual temp.)
User interface Active carbon filters (ensuring optimal air quality)	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-con-
User interface Active carbon filters (ensuring optimal air quality) Compressor	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-controlled) R600a (environment friendly) Yes
User interface Active carbon filters (ensuring optimal air quality) Compressor Coolant	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-controlled) R600a (environment friendly)
User interface Active carbon filters (ensuring optimal air quality) Compressor Coolant Vibrationfree implementation	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-controlled) R600a (environment friendly) Yes Combined fan and convection
User interface Active carbon filters (ensuring optimal air quality) Compressor Coolant Vibrationfree implementation Cooling system	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-controlled) R600a (environment friendly) Yes Combined fan and convection cooling
User interface Active carbon filters (ensuring optimal air quality) Compressor Coolant Vibrationfree implementation Cooling system Defrost function Temperatur Memory Function	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-controlled) R600a (environment friendly) Yes Combined fan and convection cooling Automatic
User interface Active carbon filters (ensuring optimal air quality) Compressor Coolant Vibrationfree implementation Cooling system Defrost function Temperatur Memory Function (Power failure)	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-controlled) R600a (environment friendly) Yes Combined fan and convection cooling Automatic Yes
User interface Active carbon filters (ensuring optimal air quality) Compressor Coolant Vibrationfree implementation Cooling system Defrost function Temperatur Memory Function (Power failure) Condensation water container	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-controlled) R600a (environment friendly) Yes Combined fan and convection cooling Automatic Yes Yes Yes (integrated powerful winter
User interface Active carbon filters (ensuring optimal air quality) Compressor Coolant Vibrationfree implementation Cooling system Defrost function Temperatur Memory Function (Power failure) Condensation water container Heating	2 digital displays (set and actual temp.) Yes Embraco Fullmotion (speed-controlled) R600a (environment friendly) Yes Combined fan and convection cooling Automatic Yes Yes Yes Yes (integrated powerful winter function)

Feet adjustable to compensate

uneven floors

Performance data	
Bottle capacity (Bordeaux shape, part of shelves removed)	55
Bottle capacity (Bordeaux shape, all shelves inserted)	47
Space for oversized bottles (Magnum, 3lt.)	On top and bottom shelf
Humidity	Recommendation 50-70%
Climate classification	SN-T
Volume	127 I
Noise level	37 dB(A) sound-absorbing re- commendation
Temperature range	5°C - 20°C
General Information	
Cooler shape	Freestanding or built-in with shadow gap
Maintenance contract (warranty extension)	Recommended
Transport weight	53 kg
Net weight	49 kg
Power consumption per day	0.285 kWh (ca.)
Voltage	220 V / 50 Hz



