

LS24A Service temperature wine cellar Service range







Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.

This equipment is designed to be used in an ambient temperature between 16 - 38°C

This appliance is intended to be used exclusively for the storage of wine.

Alcohol abuse is dangerous for health, please consume in moderation.

*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 3 shelves. Adding shelves reduce considerably the total capacity.

capacity.

**Thanks to the Vinotag® application, benefit from a digital register of your wine cellar and be alerted of the peak dates of your wines. In partnership with Vivino, scan your bottle to access its pre-filled wine sheet.

- + Capacity: 23 bottles*
- ♣ Vinotag compatible**
- Free standing installation
- Design: black body & stainless steel door frame
- Cooling system: compressor
- Type of cold: air moving system
- Adjustable temperature range of use: 5 20°C
- Electronic regulation
- Thermometer with blue digital display
- ♣ White LED lights with switch button
- 1 glass door, anti-UV treated, 2-layers tempered glass (grey-colored)

DESIGN AND PERFORMANCE

Modern, the LS24A protects your wines with its tempered glass door, anti-UV treatment and enhances your bottles with interior LED lighting. Its Black an silver look and its glazed door make it a real moderne and robust decorative object.

TO THE NEAREST DEGREE

Bring your wines to tasting temperature to take full advantage of all their aromas. The digital control panel enables a more intuitive use.

OPTIMIZED STORAGE

Store your wines on its steel shelves; up to 23 Bordeaux 75 cl bottles; removable they adapt to your needs.

EASY INSTALLATION

Its compact format guarantees a storage capacity of up to 23 Bordeaux 75cl bottles. Free-standing, it can be set easily into your interior.



LS24A Service temperature wine cellar Service range



> EQUIPMENTS INCLUDED

- 3 fixed wire shelves
- 1 semi-sliding wire half-shelf
- 2 adjustable feet (height 1.9 cm)
- 2 wheels
- Anti-vibration system

> TECHNICAL CHARACTERISTICS

■ Energy class: G

■ Annual electrical consumption: 136 kWh

Climatic class: ST
Noise level: 42 dB
Voltage: 220-240 V
Power input: 90 W
Category: 2 - Wine cellar
Type of gas: R600a

> SAFETY

■ Child lock: locks the control panel

> VINOTAG® APPLICATION

Free wine cellar management application. Access a virtual representation of your wine cellar and a detailed inventory of its contents.

> LOGISTIC DATAS

Gross dimensions (WxDxH cm) : 51 x 46 x 66,5

Net dimensions (WxDxH cm) : 48 x 43 x 63

Gross weight (kg) : 24.00

Net weight (kg) : 22.02

Full truck (pcs) : 224

Container (pcs) 20' : 165

40' : 345

40' : 345 40' HC : 460

Gencod 3541361607097

> COMPATIBLE ACCESSORIES

Only available in spare parts

Non-contractual pictures Last update: 10/02/2023