

# **BundyPlus**™

### **Electronic Time Clock**

## **Model: G6 Series**







G6-BIO-B or G6-BIO-G

**G6-PROX-G** 

G6-MAG-G

(The G6-Series time clocks are available in either grey or beige)

The BundyPlus™ G6-Series time clock is the perfect solution for today's small-medium business T&A, Access Control and Job Costing requirements. The G6-Series accurately time stamps all employee activities 24-7 so you're always in control.

- Robust Australian Made Time Clock Hardware
- Biometric(Finger Print), proximity and magnetic employee card models available
- Industry standard communications (Ethernet, WiFi, USB or 3G / GSM)
- BundyPlus <sup>™</sup> Time and Attendance application software available
- Combines over 20 years of hardware/software experience
- Proudly designed, manufactured and supported in Australia!

The BundyPlus™ G6-Series is simply one of most flexible, easy to install and cost effective electronic time clocks on the market today.

## Key Features

Low cost

Two colour options (Beige & Dark Grey) 1,000 Employee ID lookup table, Identify or Verify Job costina

Multi-card formats (magstripe, prox, barcode)\* 5 hour operational backup (UPS)\*

Access control

Industry standard communications

F1-F4 function keys Large backlit graphic LCD 2 year data retention 2 x relay outputs (meal break siren, door latch) Local support Designed & Manufactured in Australia

Direct keypad entry

12 month warranty

(\*Optional accessories)

G6-Series-datasheet.docx Page 1



# **BundyPlus**™

## **Electronic Time Clock**

## **Model: G6 Series**

#### Software

#### **Employee database**

Max employees: 1000

Employee ID, name, and message length: 30

#### **Costing database**

Max costing codes: 200

Max costing code and message length: 30

#### **Card Configuration**

Keypad: Enable or Disable Proximity card type selection

Remove leading zeros: Enable or Disable

Validation: Enable, Disable

Card direction (IN/OUT): Enable or Disable

#### Relay events

Configurable relay events (meal break notification): 50

#### **Access Control**

Access: Disabled, Only if valid, or Any

Relay period: 1-30 seconds

#### **Job Costing**

Prompt: Disabled, Only on IN, Only on OUT, ANY,

and manual entry.

Validation: Enable or Disable Fixed costing: Enable or Disable

#### Display

Time format: 24hr or 12hr.

Display seconds: Enable or Disable.

Display employee name period: Short, medium & long Display employee message period: Short, medium &

long

#### Sound

Buzzer: Enable or Disable.

Logging

Number of swipes.

Number of battery charges

Operating period

### Hardware

#### **Network Interfaces**

10/100Base-T Ethernet Auto-sensing when using

compatible network cable\*

USB

802.11b WiFi WLAN\*

3G\*

Host RS232 (3 wire 9600,n,8,1) External reader (3 wire 9600,n,8,1)

#### **Display & Indicators**

128 x 64 pixel backlit graphic LCD 10/100Base-T Ethernet link & speed LED\* 87dB buzzer

#### **Data Entry**

Direct keypad

1 x Track II magnetic swipe card\*

2 x Proximity card (HID 26bit, HID 32bit, HID36bit, HID 37bit, TCOM 26bit, ASR-27bit and custom formats)\*

**Relay Outputs** 24V AC/DC 1AMP MAX! (Note: ensure back EMF diode is fitted on non-resistive loads)

#### Connectors

Relays 5.08mm pitch screw terminals

Proximity reader: 5 way 5.08mm pitch screw terminal

Power: 2 way 5.08mm pitch detachable plug

10/100Base-T Ethernet: RJ45\*

Host RS232: RJ11

External RS232 reader: RJ11 UPS battery: 2 way 0.1" detachable

#### Installation

Hinged front cover with optional security key access cable duct entry top, bottom & rear

#### Warranty

12 months return to base

G6-Series-datasheet.docx Page 2



# **BundyPlus**™

## **Electronic Time Clock**

## **Model: G6 Series**

## Physical & Environmental

#### **Power Voltage**

12VDC 1AMP (plug pack supplied)

#### **Dimensions**

130(W) x 218\*(H) x 54(D) mm (\*not including antenna if fitted)

#### **Operating Temperature**

0°C - 50°C

#### **Storage Temperature**

-20°C - 50°C

#### **Operating Humidity**

5% - 95% non-condensing

#### Weight

2.2kgs

#### MTRF

194,238 hours @ 25°C (MIL-HDBK-217)

## **Ordering Information**

G6-BIO Biometric time clock.
G6-PROX Proximity time clock.
G6-MAG Magstripe time clock.

#### \*Optional Accessories

BP-ETHERNET 10/100Base-T Ethernet module

BP-WIFI IEEE 802.11b WiFi module

**BP-BATT** 5hour operational backup battery

BP-3G 3G modem

BP-BELL 90dB meal break bell

MAG-II Track II 10 pack magnetic cards

MAG-II(30) Track II 30 pack magnetic cards

**HID-II** Proximity card (thick)

**HID-ISO** Proximity card (thin)

**HID-FOB** Proximity fob

BP-CARDRACK wall mounted 2x25 card rack

## **Distributor**

#### Designed and manufactured by:

Midnight Technologies Pty Ltd 1<sub>st</sub> Floor, 8 Queen Street, Nunawading Victoria 3131, Melbourne Australia

#### www.bundyplus.com.au

BundyPlus  $^{\text{TM}}$  is a registered trade mark of midnight technologies pty ltd

Specifications are subject to change without notice

G6-Series-datasheet.docx Page 3