# Product datasheet



# QUICKTRONIC PROStart T5HO High Temperature

# 52665 / QHE4X54T5HOUNVPSNHTSCLDOE



QUICKTRONIC High Efficiency (QHE) PROStart T5HO High Ambient Temperature electronic ballasts operate PENTRON HO, PENTRON HO Circline, and DULUX L T5 lamps saving >2 wattsSpecifically designed for applications where the ballast is subjected to higher ambient temperatures, as in high bay industrial installations.

#### Product family features

- High Efficiency Systems over 90% efficient
- 90°C maximum case temp.
- Universal voltage (120-277V)
- 1.0 ballast factor
- QUICKSENSE ballast technology (end-of-lamp-life sensing)
- PROStart program rapid start
- UL type CC rated
- -20°F (-29C) min. starting temp., operates at >42 kHz to reduce potential interference with infrared control systems
- RoHS compliant

#### Areas of application

- Industrial high-bay
- Commercial
- Retail
- Hospitality
- Institutional
- New construction

### Technical data

## General product information

Product Name	QHE4X54T5HOUNVPSNHTSCLDOE 10/CS 1/SKU		
Ordering Abbreviation	QHE4X54T5HOUNVPSNHTSCLDOE		
Brand Name	OSRAM		
General Description	High efficiency 4 lamp Program Start UNV voltage with leads in a 10 pack that runs 4 or 3 54 W lamps, DOE compliant		
Product Number	52665		

### **Electrical data**

Nominal Total Max Wattage	241 W
Power Factor	>0.97
Open Circuit Voltage (V)	<600 V
Wiring Method	Leads

# Dimensions & weight

Dimensions	Slim Can L
Ballast Height (in)	1.1800 in
Ballast Length (in)	16.1730 in
Ballast Width (in)	1.6800 in

# Temperatures & operating conditions

Starting Temperature - Celsius	-29 C
Starting Temperature - Fahrenheit	-20.2 F
Maximum Case Temperature	70 C

## Additional product data

Sound Rating	A	
Starting Method	Programmed Start	
Primary Lamp Type 1	FP54T5HO	
Total Harmonic Distortion (THD)	<10	

### Light management & control

Circuit Type

Series

### QTP PROStart T5HO 0.80BF UNV Systems

QHE T5HO PSN HT UNV Systems

#### Packaging Information

Item number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
52665	4052899266339	Unpacked (SKU)	1		
52665	4052899266346	Shipping box (Case)	10	18.2 in x 12.8 in x 2.6 in	30.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

For information on specific product warranties, visit www.osram.us/warranty. Specifications are subject to change without notice.OSRAM and QUICKTRONIC are registered trademarks of OSRAM GmbH.SYLVANIA is a registered trademark of OSRAM SYLVANIA Inc.SUBSTITRONIC is a trademark of OSRAM SYLVANIA Inc.All other trademarks are those of their respective owners.