

Commercial Grade  
  Medium Ceilings  
  Heavy Duty  
  Energy Efficient

## Applications

- Warehouses
- Retail
- Aisles

## Benefits

- High Efficiency
- Up to 90% Energy Savings
- Epcat and Utility Rebates

## Features

- Tool-free Ballast Access
- 25 Year Reflector Warranty
- ETL Certified

## Photometry

- 2 Lamp 4' - FSL-023204-EAN
- Efficiency: 91.2%
- 0-DEG: 1.2
- 90-DEG: 1.7
- Report Number: 1406



## Design

- Made in the USA
- Dimensions: 2.50" x 8.875" x 48.00"
- Designed for surface, chain, gripple mount; pendant mount optional
- Fixture body and ends are post painted and will not rust
- Knockouts on housing back or ends
- Reflector attaches with quarter turns for easy maintenance
- Sockets snap-in & twist-lock
- CEE approved electronic ballast
- Wire guard option available
- End mounted sensor available
- ETL Certified

Conversion Chart		
T8 Fixture Configuration	System Wattage	Lumens
1 Lamp F32 T8 Normal	28	2950
1 Lamp F32 T8 High	41	3600
2 Lamp F28 T8 Normal	57	5192
2 Lamp F28 T8 Low	51	4602
2 Lamp F32 T8 High	75	6961
4 Lamp F32 T8 Normal	113	10,384
4 Lamp F32 T8 Low	102	9440
4 Lamp F32 T8 High	146	13,923
T5 Fixture Configuration	System Wattage	Lumens
1 Lamp F28 T5 Normal	26	2900
2 Lamp F28 T5 Normal	60	5568
2 Lamp F54 T5 High	114	10,000
4 Lamp F54 T5 High	216	20,000

\*Lamp/ballast information provided from GE based on F32 lamp.  
Other lamp types produce additional energy savings.

## Fixture Ordering Guide Example

### FSL-023204-EAN

Series	Lamps	Wattage	Length	Material	Power Factor
FSL	01 - 1 Lamp	14 - 14W T5	02 - 2'	EA - 95% Enhanced Aluminum	H - High
	02 - 2 Lamp	17 - 17W T8	04 - 4'	SA - 86% Specular Aluminum	N - Normal
	03 - 3 Lamp	25 - 25W T8	08 - 8'	WA - 91% White Aluminum	L - Low
	04 - 4 Lamp	28 - 28W T5			4 - 480 Volt
	06 - 6 Lamp	32 - 32W T8			
			54 - 54W T5		

## Option Ordering Guide

See Standard Option Guide



Industry Leader in  
Customization + Lead Times  
for Over 25 Years

VIDALIA, GA  
1-800-537-1629

