

GREEN LAWNGER®

Premium Turf Paint and Divot Mix Colorant

Green Lawnger® turf colorant with ColorLock technology restores the natural green color to turf during dormant periods. Green Lawnger colorant is a permanent green pigment, not a dye, which contains no hazardous chemicals, heavy metals, or other inert ingredients harmful to turf. Green Lawnger colorant may also be pre-applied to divot mix sand, giving the mix a natural green color.

PACKAGING

Available in 12 x 1 liter, 4 x 1 gallon, 2 x 2.25 gallon, and 30 gallon drum.

RECOMMENDED RATES

One gallon (3.78 L) concentrate of Green Lawnger colorant will treat 4,000 to 12,000 sq. ft. (370-1,115 sq. m) of turf when mixed with water.

The area covered will vary with the rate of Green Lawnger colorant used, type and condition of grass being treated, and turf color desired.

Typically a 1:7 colorant to water ratio is recommended on dormant turf, and a 1:15 ratio on other turf.

DIRECTIONS FOR USE

Before applying Green Lawnger colorant, cut turf to desired height.

For best results, cover leaf blade completely with fine particle-size droplets using flat fan spray nozzles. Avoid excessive run off from the leaf blade to soil surfaces.

Nozzle types, pressure, flow rate and spray angle will all affect product distribution.

Dormant (Fall) Application: Dilute one gallon (3.78 L) Green Lawnger colorant with 7-9 gallons (26-34 L) water. For a darker turf color, reduce volume of water. Some experimentation may be required with the water to colorant ratio to obtain the exact color desired.

Non-Dormant (Summer) Application: Dilute one gallon (3.78 L) with 15-20 gallons (56-75 L) water. Again, the application rate depends on the desired color. For best results on any discolored area, two applications are recommended to blend the colored area in with the surrounding healthy turf.

Divot Mix Sand: Mix 6 ounces (177 mL) of Green Lawnger with same volume water. Spray or pour the solution onto 100 lbs. (45 kg) of divot mix sand in a cement-type mixer. Mix until colored. Adjust the colorant to water ratio to achieve the desired color.

Avoid over-spray on concrete, masonry, or any other objects where color is not desired. Permanent staining may occur. Accidental over-spray may be removed by a water rinse prior to drying.

Equipment Notice: Becker Underwood recommends the use of Teflon seals to aid in the prevention of leaks when using Green Lawnger colorant in centrifugal pumps. Standard ceramic seals may leak during operation. For best results, use low to medium sprayer pressure.

Rinse spray tank, spray nozzles, and screens thoroughly with water immediately following use.

If this product is mixed with pesticides, the entire mixture, including rinsate, must be handled and disposed of according to all applicable local, state, and federal guidelines.

®,™ Trademarks, registered or applied for, of Becker Underwood, Inc., Ames, IA. Rev. 11/8/12.