



# Dy-Mark Landscape Chalk All Colours

Dy-Mark

Chemwatch Hazard Alert Code: 4

Chemwatch: 4649-18

Version No: 13.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: 23/08/2016

Print Date: 26/08/2016

S.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | Dy-Mark Landscape Chalk All Colours  |
| Synonyms                      | 23183502 Red, 23183503 Blue, 23183504 Green, 23183505 Yellow, 23183506 Orange, 23183511 White, 23183529 Fluro Pink |
| Proper shipping name          | AEROSOLS   |
| Other means of identification | Not Available  |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |  |
|--------------------------|--|
| Relevant identified uses | Application is by spray atomisation from a hand held aerosol pack<br>Temporary marking aerosol |
|--------------------------|--|

### Details of the supplier of the safety data sheet

|                         |  |
|-------------------------|--|
| Registered company name | Dy-Mark                                      |
| Address                 | 89 Formation Street Wacol QLD 4076 Australia |
| Telephone               | +61 7 3271 2222                              |
| Fax                     | +61 7 3271 2751                              |
| Website                 | Not Available                                |
| Email                   | info@dymark.com.au                           |

### Emergency telephone number

|                                   |                 |
|-----------------------------------|-----------------|
| Association / Organisation        | Not Available   |
| Emergency telephone numbers       | +61 403 186 708 |
| Other emergency telephone numbers | Not Available   |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. DANGEROUS GOODS.** According to the WHS Regulations and the ADG Code.

#### CHEMWATCH HAZARD RATINGS

|              | Min | Max |
|--------------|-----|-----|
| Flammability | 4   |     |
| Toxicity     | 1   |     |
| Body Contact | 2   |     |
| Reactivity   | 1   |     |
| Chronic      | 0   |     |

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

|                               |   |
|-------------------------------|---|
| Poisons Schedule              | Not Applicable  |
| Classification <sup>[1]</sup> | Aerosols Category 1, Eye Irritation Category 2A, Specific target organ toxicity - single exposure Category 3 (narcotic effects) |
| Legend:                       | 1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI  |

### Label elements

|                    |  |
|--------------------|--|
| GHS label elements |  |
|--------------------|--|

|             |               |
|-------------|---------------|
| SIGNAL WORD | <b>DANGER</b> |
|-------------|---------------|

### Hazard statement(s)

Continued...

|        |   |
|--------|---|
| H222   | Extremely flammable aerosol.                          |
| H319   | Causes serious eye irritation.                        |
| H336   | May cause drowsiness or dizziness.                    |
| AUH044 | Risk of explosion if heated under confinement         |
| AUH066 | Repeated exposure may cause skin dryness and cracking |

**Supplementary statement(s)**

Not Applicable

**Precautionary statement(s) Prevention**

|      |  |
|------|--|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P211 | Do not spray on an open flame or other ignition source.            |
| P251 | Pressurized container: Do not pierce or burn, even after use.      |
| P271 | Use only outdoors or in a well-ventilated area.                    |

**Precautionary statement(s) Response**

|                |  |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER or doctor/physician if you feel unwell.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P304+P340      | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                 |

**Precautionary statement(s) Storage**

|           |  |
|-----------|--|
| P405      | Store locked up.   |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed.             |

**Precautionary statement(s) Disposal**

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No      | %[weight] | Name                          |
|-------------|-----------|-------------------------------|
| 67-64-1     | 30-60     | <u>acetone</u>                |
| 123-86-4    | 1-10      | <u>n-butyl acetate</u>        |
| 64-17-5     | <1        | <u>ethanol</u>                |
| 115-10-6    | 10-30     | <u>dimethyl ether</u>         |
| 68476-85-7. | 10-30     | <u>hydrocarbon propellant</u> |

**SECTION 4 FIRST AID MEASURES****Description of first aid measures**

|                     |   |
|---------------------|---|
| <b>Eye Contact</b>  | <p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>   |
| <b>Skin Contact</b> | <p>If solids or aerosol mists are deposited upon the skin:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Remove any adhering solids with industrial skin cleansing cream.</li> <li>▶ <b>DO NOT use solvents.</b></li> <li>▶ Seek medical attention in the event of irritation.</li> </ul>   |
| <b>Inhalation</b>   | <p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> <li>▶ Remove to fresh air.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul> |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> </ul> <p>Not considered a normal route of entry.</p>  |

**Indication of any immediate medical attention and special treatment needed**

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

## Dy-Mark Landscape Chalk All Colours

- ▶ Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- ▶ Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

Treat symptomatically.

for lower alkyl ethers:

### BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ A low-stimulus environment must be maintained.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Anticipate and treat, where necessary, for seizures.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

### ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension without signs of hypovolaemia may require vasopressors.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

### EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Ethers may produce anion gap acidosis. Hyperventilation and bicarbonate therapy might be indicated.
- ▶ Haemodialysis might be considered in patients with impaired renal function.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For acute or short term repeated exposures to acetone:

- ▶ Symptoms of acetone exposure approximate ethanol intoxication.
- ▶ About 20% is expired by the lungs and the rest is metabolised. Alveolar air half-life is about 4 hours following two hour inhalation at levels near the Exposure Standard; in overdose, saturable metabolism and limited clearance, prolong the elimination half-life to 25-30 hours.
- ▶ There are no known antidotes and treatment should involve the usual methods of decontamination followed by supportive care. [Ellenhorn and Barceloux: Medical Toxicology]

Management:

Measurement of serum and urine acetone concentrations may be useful to monitor the severity of ingestion or inhalation.

Inhalation Management:

- ▶ Maintain a clear airway, give humidified oxygen and ventilate if necessary.
- ▶ If respiratory irritation occurs, assess respiratory function and, if necessary, perform chest X-rays to check for chemical pneumonitis.
- ▶ Consider the use of steroids to reduce the inflammatory response.
- ▶ Treat pulmonary oedema with PEEP or CPAP ventilation.

Dermal Management:

- ▶ Remove any remaining contaminated clothing, place in double sealed, clear bags, label and store in secure area away from patients and staff.
- ▶ Irrigate with copious amounts of water.
- ▶ An emollient may be required.

Eye Management:

- ▶ Irrigate thoroughly with running water or saline for 15 minutes.
- ▶ Stain with fluorescein and refer to an ophthalmologist if there is any uptake of the stain.

Oral Management:

- ▶ No **GASTRIC LAVAGE OR EMETIC**
- ▶ Encourage oral fluids.

Systemic Management:

- ▶ Monitor blood glucose and arterial pH.
- ▶ Ventilate if respiratory depression occurs.
- ▶ If patient unconscious, monitor renal function.
- ▶ Symptomatic and supportive care.

The Chemical Incident Management Handbook:

Guy's and St. Thomas' Hospital Trust, 2000

### BIOLOGICAL EXPOSURE INDEX

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

| Determinant      | Sampling Time | Index   | Comments |
|------------------|---------------|---------|----------|
| Acetone in urine | End of shift  | 50 mg/L | NS       |

NS: Non-specific determinant; also observed after exposure to other material

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

#### SMALL FIRE:

- ▶ Water spray, dry chemical or CO<sub>2</sub>

#### LARGE FIRE:

- ▶ Water spray or fog.

### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

### Advice for firefighters

|                              |   |
|------------------------------|---|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> </ul>   |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat or flame.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li> </ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) other pyrolysis products typical of burning organic material <b>Contains low boiling substance:</b> Closed containers may rupture due to pressure buildup under fire conditions.</p> |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Wear protective clothing, impervious gloves and safety glasses.</li> <li>▶ Shut off all possible sources of ignition and increase ventilation.</li> </ul>  |
| <b>Major Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove leaking cylinders to a safe place if possible.</li> <li>▶ Release pressure under safe, controlled conditions by opening the valve.</li> <li>▶ <b>DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.</b></li> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> </ul>                           |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li> <li>▶ Store in original containers in approved flammable liquid storage area.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Keep containers securely sealed.</li> </ul> |

### Conditions for safe storage, including any incompatibilities

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ Aerosol dispenser.</li> <li>▶ Check that containers are clearly labelled.</li> </ul> |
| <b>Storage incompatibility</b> | ▶ Avoid reaction with oxidising agents  |



+ X X X + + +

- X** — Must not be stored together  
**0** — May be stored together with specific preventions  
**+** — May be stored together

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

|| OCCUPATIONAL EXPOSURE LIMITS (OEL)

|| INGREDIENT DATA

## Dy-Mark Landscape Chalk All Colours


| Source                       | Ingredient             | Material name                 | TWA                               | STEL                              | Peak          | Notes         |
|------------------------------|------------------------|-------------------------------|-----------------------------------|-----------------------------------|---------------|---------------|
| Australia Exposure Standards | acetone                | Acetone                       | 1185 mg/m <sup>3</sup> / 500 ppm  | 2375 mg/m <sup>3</sup> / 1000 ppm | Not Available | Not Available |
| Australia Exposure Standards | n-butyl acetate        | n-Butyl acetate               | 713 mg/m <sup>3</sup> / 150 ppm   | 950 mg/m <sup>3</sup> / 200 ppm   | Not Available | Not Available |
| Australia Exposure Standards | ethanol                | Ethyl alcohol                 | 1880 mg/m <sup>3</sup> / 1000 ppm | Not Available                     | Not Available | Not Available |
| Australia Exposure Standards | dimethyl ether         | Dimethyl ether                | 760 mg/m <sup>3</sup> / 400 ppm   | 950 mg/m <sup>3</sup> / 500 ppm   | Not Available | Not Available |
| Australia Exposure Standards | hydrocarbon propellant | LPG (liquefied petroleum gas) | 1800 mg/m <sup>3</sup> / 1000 ppm | Not Available                     | Not Available | Not Available |

## EMERGENCY LIMITS

| Ingredient             | Material name                     | TEEL-1        | TEEL-2        | TEEL-3        |
|------------------------|-----------------------------------|---------------|---------------|---------------|
| acetone                | Acetone                           | Not Available | Not Available | Not Available |
| n-butyl acetate        | Butyl acetate, n-                 | Not Available | Not Available | Not Available |
| ethanol                | Ethyl alcohol; (Ethanol)          | Not Available | Not Available | Not Available |
| dimethyl ether         | Methyl ether; (Dimethyl ether)    | 1,000 ppm     | 1000 ppm      | 7200 ppm      |
| hydrocarbon propellant | Liquefied petroleum gas; (L.P.G.) | 3,000 ppm     | 3200 ppm      | 19000 ppm     |

| Ingredient             | Original IDLH    | Revised IDLH    |
|------------------------|------------------|-----------------|
| acetone                | 20,000 ppm       | 2,500 [LEL] ppm |
| n-butyl acetate        | 10,000 ppm       | 1,700 [LEL] ppm |
| ethanol                | 15,000 ppm       | 3,300 [LEL] ppm |
| dimethyl ether         | Not Available    | Not Available   |
| hydrocarbon propellant | 19,000 [LEL] ppm | 2,000 [LEL] ppm |

## Exposure controls

|   |   |
|---|---|
| <b>Appropriate engineering controls</b> | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>  |
| <b>Personal protection</b>              |    |
| <b>Eye and face protection</b>          | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>   |
| <b>Skin protection</b>                  | See Hand protection below   |
| <b>Hands/feet protection</b>            | <ul style="list-style-type: none"> <li>▶ No special equipment needed when handling small quantities.</li> <li>▶ <b>OTHERWISE:</b></li> <li>▶ For potentially moderate exposures:</li> <li>▶ Wear general protective gloves, eg. light weight rubber gloves.</li> <li>▶ For potentially heavy exposures:</li> <li>▶ Wear chemical protective gloves, eg. PVC. and safety footwear.</li> </ul>  |
| <b>Body protection</b>                  | See Other protection below  |
| <b>Other protection</b>                 | <ul style="list-style-type: none"> <li>▶ The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.</li> <li>▶ Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.</li> </ul> <p>BREITHERICK: Handbook of Reactive Chemical Hazards.</p> <p>Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</p> <p>For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</p> <p>Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.</p> <p>No special equipment needed when handling small quantities.</p> <p><b>OTHERWISE:</b></p> <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eyewash unit.</li> </ul> |
| <b>Thermal hazards</b>                  | Not Available   |

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Dy-Mark Landscape Chalk All Colours

| Material  | CPI     |
|-----------|---------|
| ##n-butyl | acetate |

## Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
|                                    |                      |                      |                        |

## Dy-Mark Landscape Chalk All Colours

|                  |       |
|------------------|-------|
| BUTYL            | C     |
| BUTYL/NEOPRENE   | C     |
| CPE              | C     |
| HYPALON          | C     |
| NATURAL RUBBER   | C     |
| NATURAL+NEOPRENE | C     |
| NEOPRENE         | C     |
| NEOPRENE/NATURAL | C     |
| NITRILE          | C     |
| NITRILE+PVC      | C     |
| PE               | C     |
| PE/EVAL/PE       | C     |
| PVA              | C     |
| PVC              | C     |
| PVDC/PE/PVDC     | C     |
| SARANEX-23       | C     |
| SARANEX-23 2-PLY | C     |
| TEFLON           | C     |
| VITON/BUTYL      | C     |
| VITON/NEOPRENE   | C     |
| ##dimethyl       | ether |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

|               |           |            |             |
|---------------|-----------|------------|-------------|
| up to 10 x ES | Air-line* | AX-2       | AX-PAPR-2 ^ |
| up to 20 x ES | -         | AX-3       | -           |
| 20+ x ES      | -         | Air-line** | -           |

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

- ▶ Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- ▶ Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|   |   |  |                |
|---|---|--|----------------|
| <b>Appearance</b>                                   | Supplied as an aerosol pack. Contents under <b>PRESSURE</b> . Contains highly flammable hydrocarbon propellant.<br> Green-yellow flammable liquid; not miscible with water. |  |                |
| <b>Physical state</b>                               | Liquid  | <b>Relative density (Water = 1)</b>            | Not Available  |
| <b>Odour</b>  | Not Available   | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available   | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Applicable  | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available   | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available   | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | -81 (propellant)  | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available   | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | HIGHLY FLAMMABLE.   | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available   | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available   | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Available   | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water (g/L)</b>                    | Immiscible  | <b>pH as a solution (1%)</b>                   | Not Applicable |
| <b>Vapour density (Air = 1)</b>                     | Not Available   | <b>VOC g/L</b>                                 | Not Available  |

## SECTION 10 STABILITY AND REACTIVITY

|                           |  |
|---------------------------|--|
| <b>Reactivity</b>         | See section 7  |
| <b>Chemical stability</b> | <ul style="list-style-type: none"> <li>▶ Elevated temperatures.</li> <li>▶ Presence of open flame.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |

Dy-Mark Landscape Chalk All Colours

|   |               |
|---|---------------|
| <b>Possibility of hazardous reactions</b> | See section 7 |
| <b>Conditions to avoid</b>                | See section 7 |
| <b>Incompatible materials</b>             | See section 7 |
| <b>Hazardous decomposition products</b>   | See section 5 |

**SECTION 11 TOXICOLOGICAL INFORMATION**

**Information on toxicological effects**

|                     |   |
|---------------------|---|
| <b>Inhaled</b>      | <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p><b>WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.</b></p> |
| <b>Ingestion</b>    | <p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Not normally a hazard due to physical form of product.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p>   |
| <b>Skin Contact</b> | <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p>  |
| <b>Eye</b>          | <p>Not considered to be a risk because of the extreme volatility of the gas.</p> <p>There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.</p>   |
| <b>Chronic</b>      | <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>Principal route of occupational exposure to the gas is by inhalation.</p>  |

|  |  |                                     |
|--|--|-------------------------------------|
| <b>Dy-Mark Landscape Chalk All Colours</b> | <b>TOXICITY</b>  | <b>IRRITATION</b>                   |
|  | Not Available  | Not Available                       |
| <b>acetone</b>                             | <b>TOXICITY</b>  | <b>IRRITATION</b>                   |
|  | Dermal (rabbit) LD50: 20000 mg/kg <sup>[2]</sup>                         | Eye (human): 500 ppm - irritant     |
|  | Inhalation (rat) LC50: 50.1 mg/L/8 hr <sup>[2]</sup>                     | Eye (rabbit): 20mg/24hr - moderate  |
|  | Oral (rat) LD50: 5800 mg/kg <sup>[2]</sup>                               | Eye (rabbit): 3.95 mg - SEVERE      |
|  |  | Skin (rabbit): 500 mg/24hr - mild   |
|  |  | Skin (rabbit): 395mg (open) - mild  |
| <b>n-butyl acetate</b>                     | <b>TOXICITY</b>  | <b>IRRITATION</b>                   |
|  | Dermal (rabbit) LD50: >14080 mg/kg <sup>[1]</sup>                        | * [PPG]                             |
|  | Inhalation (rat) LC50: 2000 ppm/4hr <sup>[2]</sup>                       | Eye (human): 300 mg                 |
|  | Inhalation (rat) LC50: 390 ppm/4hr <sup>[2]</sup>                        | Eye (rabbit): 20 mg (open)-SEVERE   |
|  | Oral (rat) LD50: 10736 mg/kg <sup>[1]</sup>                              | Eye (rabbit): 20 mg/24h - moderate  |
|  |  | Skin (rabbit): 500 mg/24hr-moderate |
| <b>ethanol</b>                             | <b>TOXICITY</b>  | <b>IRRITATION</b>                   |
|  | Dermal (rabbit) LD50: 17100 mg/kg <sup>[1]</sup>                         | Eye (rabbit): 500 mg SEVERE         |
|  | Inhalation (rat) LC50: 64000 ppm/4hr <sup>[2]</sup>                      | Eye (rabbit): 100mg/24hr-moderate   |
|  | Oral (rat) LD50: >1187-2769 mg/kg <sup>[1]</sup>                         | Skin (rabbit): 20 mg/24hr-moderate  |
|  |  | Skin (rabbit): 400 mg (open)-mild   |
| <b>dimethyl ether</b>                      | <b>TOXICITY</b>  | <b>IRRITATION</b>                   |
|  | Inhalation (rat) LC50: 309 mg/L/4hr <sup>[2]</sup>                       | Nil reported                        |
| <b>hydrocarbon propellant</b>              | <b>TOXICITY</b>  | <b>IRRITATION</b>                   |
|  | Inhalation (mouse) LC50: >15.6-<17.9 mm <sup>3</sup> /2hr <sup>[1]</sup> | Not Available                       |
|  | Inhalation (mouse) LC50: >15.6-<17.9 mm <sup>3</sup> /2hr <sup>[1]</sup> |                                     |
|  | Inhalation (mouse) LC50: 410000 ppm/2hr <sup>[1]</sup>                   |                                     |

## Dy-Mark Landscape Chalk All Colours

|   |
|---|
| Inhalation (mouse) LC50: 410000 ppm/2hr <sup>[1]</sup>    |
| Inhalation (rat) LC50: >800000 ppm15 min <sup>[1]</sup>   |
| Inhalation (rat) LC50: >800000 ppm15 min <sup>[1]</sup>   |
| Inhalation (rat) LC50: 1354.944 mg/L15 min <sup>[1]</sup> |
| Inhalation (rat) LC50: 1355 mg/15 min <sup>[1]</sup>      |
| Inhalation (rat) LC50: 1442.738 mg/L15 min <sup>[1]</sup> |
| Inhalation (rat) LC50: 1442.738 mg/L15 min <sup>[1]</sup> |
| Inhalation (rat) LC50: 1443 mg/15 min <sup>[1]</sup>      |
| Inhalation (rat) LC50: 1443 mg/15 min <sup>[1]</sup>      |
| Inhalation (rat) LC50: 570000 ppm15 min <sup>[1]</sup>    |

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|  |   |
|--|---|
| <b>N-BUTYL ACETATE</b>   | The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.  |
| <b>HYDROCARBON PROPELLANT</b>  | No significant acute toxicological data identified in literature search. inhalation of the gas  |
| <b>Dy-Mark Landscape Chalk All Colours &amp; ACETONE &amp; N-BUTYL ACETATE &amp; ETHANOL</b> | The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.  |
| <b>Dy-Mark Landscape Chalk All Colours &amp; ACETONE</b>                                     | for acetone:<br>The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitiser but is a defatting agent to the skin. Acetone is an eye irritant. The subchronic toxicity of acetone has been examined in mice and rats that were administered acetone in the drinking water and again in rats treated by oral gavage. |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ☹ | <b>Carcinogenicity</b>          | ☹ |
| <b>Skin Irritation/Corrosion</b>         | ☹ | <b>Reproductivity</b>           | ☹ |
| <b>Serious Eye Damage/Irritation</b>     | ✔ | <b>STOT - Single Exposure</b>   | ✔ |
| <b>Respiratory or Skin sensitisation</b> | ☹ | <b>STOT - Repeated Exposure</b> | ☹ |
| <b>Mutagenicity</b>                      | ☹ | <b>Aspiration Hazard</b>        | ☹ |

**Legend:** ✖ – Data available but does not fill the criteria for classification  
✔ – Data required to make classification available  
☹ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| Ingredient             | Endpoint | Test Duration (hr) | Species                       | Value         | Source |
|------------------------|----------|--------------------|-------------------------------|---------------|--------|
| acetone                | LC50     | 96                 | Fish                          | >100mg/L      | 4      |
| acetone                | EC50     | 48                 | Crustacea                     | >100mg/L      | 4      |
| acetone                | EC50     | 96                 | Algae or other aquatic plants | 20.565mg/L    | 4      |
| acetone                | EC50     | 384                | Crustacea                     | 97.013mg/L    | 3      |
| acetone                | NOEC     | 96                 | Algae or other aquatic plants | 4.950mg/L     | 4      |
| n-butyl acetate        | LC50     | 96                 | Fish                          | 18mg/L        | 2      |
| n-butyl acetate        | EC50     | 48                 | Crustacea                     | ≈32mg/L       | 1      |
| n-butyl acetate        | EC50     | 96                 | Algae or other aquatic plants | 1.675mg/L     | 3      |
| n-butyl acetate        | EC50     | 96                 | Fish                          | 18mg/L        | 2      |
| n-butyl acetate        | NOEC     | 504                | Crustacea                     | 23mg/L        | 2      |
| ethanol                | LC50     | 96                 | Fish                          | 42mg/L        | 4      |
| ethanol                | EC50     | 48                 | Crustacea                     | 2mg/L         | 4      |
| ethanol                | EC50     | 72                 | Algae or other aquatic plants | 275mg/L       | 2      |
| ethanol                | EC50     | 24                 | Algae or other aquatic plants | 0.0129024mg/L | 4      |
| ethanol                | NOEC     | 2016               | Fish                          | 0.000375mg/L  | 4      |
| dimethyl ether         | LC50     | 96                 | Fish                          | 200.592mg/L   | 3      |
| dimethyl ether         | EC50     | 48                 | Crustacea                     | >4400.0mg/L   | 2      |
| dimethyl ether         | EC50     | 96                 | Algae or other aquatic plants | 154.917mg/L   | 2      |
| dimethyl ether         | EC50     | 384                | Crustacea                     | 46.027mg/L    | 3      |
| dimethyl ether         | NOEC     | 48                 | Crustacea                     | >4000mg/L     | 1      |
| hydrocarbon propellant | LC50     | 96                 | Fish                          | 24.11mg/L     | 2      |

Continued...



Dy-Mark Landscape Chalk All Colours

|                        |      |    |                               |           |   |
|------------------------|------|----|-------------------------------|-----------|---|
| hydrocarbon propellant | EC50 | 96 | Algae or other aquatic plants | 7.71mg/L  | 2 |
| hydrocarbon propellant | EC50 | 96 | Algae or other aquatic plants | 8.57mg/L  | 2 |
| hydrocarbon propellant | LC50 | 96 | Fish                          | 24.11mg/L | 2 |
| hydrocarbon propellant | EC50 | 96 | Algae or other aquatic plants | 7.71mg/L  | 2 |
| hydrocarbon propellant | EC50 | 96 | Algae or other aquatic plants | 8.57mg/L  | 2 |

**Legend:**

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

**Persistence and degradability**

| Ingredient      | Persistence: Water/Soil     | Persistence: Air                 |
|-----------------|-----------------------------|----------------------------------|
| acetone         | LOW (Half-life = 14 days)   | MEDIUM (Half-life = 116.25 days) |
| n-butyl acetate | LOW                         | LOW                              |
| ethanol         | LOW (Half-life = 2.17 days) | LOW (Half-life = 5.08 days)      |
| dimethyl ether  | LOW                         | LOW                              |

**Bioaccumulative potential**

| Ingredient      | Bioaccumulation      |
|-----------------|----------------------|
| acetone         | LOW (BCF = 0.69)     |
| n-butyl acetate | LOW (BCF = 14)       |
| ethanol         | LOW (LogKOW = -0.31) |
| dimethyl ether  | LOW (LogKOW = 0.1)   |

**Mobility in soil**

| Ingredient      | Mobility           |
|-----------------|--------------------|
| acetone         | HIGH (KOC = 1.981) |
| n-butyl acetate | LOW (KOC = 20.86)  |
| ethanol         | HIGH (KOC = 1)     |
| dimethyl ether  | HIGH (KOC = 1.292) |

**SECTION 13 DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | <ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Discharge contents of damaged aerosol cans at an approved site.</li> <li>▶ Allow small quantities to evaporate.</li> <li>▶ <b>DO NOT</b> incinerate or puncture aerosol cans.</li> </ul> |
|-------------------------------------|--|

**SECTION 14 TRANSPORT INFORMATION**

**Labels Required**

|   |                |
|---|----------------|
|  |                |
| <b>Marine Pollutant</b>   | NO             |
| <b>HAZCHEM</b>  | Not Applicable |

**Land transport (ADG)**

|                                   |  |       |     |         |                |
|-----------------------------------|--|-------|-----|---------|----------------|
| <b>UN number</b>                  | 1950   |       |     |         |                |
| <b>UN proper shipping name</b>    | AEROSOLS   |       |     |         |                |
| <b>Transport hazard class(es)</b> | <table border="0"> <tr> <td>Class</td> <td>2.1</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table> | Class | 2.1 | Subrisk | Not Applicable |
| Class                             | 2.1  |       |     |         |                |
| Subrisk                           | Not Applicable   |       |     |         |                |
| <b>Packing group</b>              | Not Applicable   |       |     |         |                |
| <b>Environmental hazard</b>       | Not Applicable   |       |     |         |                |

## Dy-Mark Landscape Chalk All Colours

|                                     |                    |                    |
|-------------------------------------|--------------------|--------------------|
| <b>Special precautions for user</b> | Special provisions | 63 190 277 327 344 |
|                                     | Limited quantity   | 1000ml             |

**Air transport (ICAO-IATA / DGR)**

|                                     |  |                              |
|-------------------------------------|--|------------------------------|
| <b>UN number</b>                    | 1950   |                              |
| <b>UN proper shipping name</b>      | Aerosols, flammable; Aerosols, flammable (engine starting fluid) |                              |
| <b>Transport hazard class(es)</b>   | ICAO/IATA Class  | 2.1                          |
|                                     | ICAO / IATA Subrisk  | Not Applicable               |
|                                     | ERG Code   | 10L                          |
| <b>Packing group</b>                | Not Applicable   |                              |
| <b>Environmental hazard</b>         | Not Applicable   |                              |
| <b>Special precautions for user</b> | Special provisions   | A145A167A802; A1A145A167A802 |
|                                     | Cargo Only Packing Instructions                                  | 203                          |
|                                     | Cargo Only Maximum Qty / Pack                                    | 150 kg                       |
|                                     | Passenger and Cargo Packing Instructions                         | 203; Forbidden               |
|                                     | Passenger and Cargo Maximum Qty / Pack                           | 75 kg; Forbidden             |
|                                     | Passenger and Cargo Limited Quantity Packing Instructions        | Y203; Forbidden              |
|                                     | Passenger and Cargo Limited Maximum Qty / Pack                   | 30 kg G; Forbidden           |

**Sea transport (IMDG-Code / GGVSee)**

|                                     |                    |                        |
|-------------------------------------|--------------------|------------------------|
| <b>UN number</b>                    | 1950               |                        |
| <b>UN proper shipping name</b>      | AEROSOLS           |                        |
| <b>Transport hazard class(es)</b>   | IMDG Class         | 2.1                    |
|                                     | IMDG Subrisk       | Not Applicable         |
| <b>Packing group</b>                | Not Applicable     |                        |
| <b>Environmental hazard</b>         | Not Applicable     |                        |
| <b>Special precautions for user</b> | EMS Number         | F-D, S-U               |
|                                     | Special provisions | 63 190 277 327 344 959 |
|                                     | Limited Quantities | 1000ml                 |

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture****ACETONE(67-64-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

**N-BUTYL ACETATE(123-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

**ETHANOL(64-17-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

**DIMETHYL ETHER(115-10-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

**HYDROCARBON PROPELLANT(68476-85-7.) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

| National Inventory | Status  |
|--------------------|---|
| Australia - AICS   | Y   |
| Canada - DSL       | Y   |
| Canada - NDSL      | N (acetone; n-butyl acetate; dimethyl ether; ethanol; hydrocarbon propellant) |

Continued...

## Dy-Mark Landscape Chalk All Colours

|                               |  |
|-------------------------------|--|
| China - IECSC                 | Y  |
| Europe - EINEC / ELINCS / NLP | Y  |
| Japan - ENCS                  | Y  |
| Korea - KECI                  | Y  |
| New Zealand - NZIoC           | Y  |
| Philippines - PICCS           | Y  |
| USA - TSCA                    | Y  |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

**SECTION 16 OTHER INFORMATION****Other information****Ingredients with multiple cas numbers**

| Name                   | CAS No                   |
|------------------------|--------------------------|
| dimethyl ether         | 115-10-6, 157621-61-9    |
| hydrocarbon propellant | 68476-85-7., 68476-86-8. |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net](http://www.chemwatch.net)

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC—TWA: Permissible Concentration-Time Weighted Average  
 PC—STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.