



SAFETY DATA SHEET CRYSTALBRITE DESTAIN PREMIUM 35

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CRYSTALBRITE DESTAIN PREMIUM 35

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Supplier Cleenol Group Ltd
Neville House
Beaumont Road
Banbury
Oxon OX16 1RB
UK
Tel : +44 (0)1295 251721
Fax : +44 (0)1295 269561
sales@cleenol.co.uk

Manufacturer Cleenol Group Ltd
Neville House
Beaumont Road
Banbury
Oxon OX16 1RB
UK
Tel : +44 (0)1295 251721
Fax : +44 (0)1295 269561
sales@cleenol.co.uk

1.4. Emergency telephone number

Emergency telephone Poisons Information Specialist
National Poisons Information Service
Birmingham
B18 7QH
Tel: 0121 507 5122

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335

Environmental hazards Not Classified

CRYSTALBRITE DESTAIN PREMIUM 35

Classification (67/548/EEC or 1999/45/EC) Xn;R22. Xi;R37/38,R41.

Human health Vapours and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Risk of serious damage to eyes. Prolonged skin contact may cause redness and irritation. May cause skin sensitisation or allergic reactions in sensitive individuals. The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

Environmental The product is not expected to be hazardous to the environment.

Physicochemical The product is flammable. Heating may generate flammable vapours.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements
 H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

Precautionary statements
 P261 Avoid breathing vapour/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with national regulations.
 P310 Immediately call a POISON CENTER/doctor.
 P311 Call a POISON CENTER/doctor.

Contains HYDROGEN PEROXIDE SOLUTION

2.3. Other hazards

Other Hazards None

SECTION 3: Composition/information on ingredients

3.2. Mixtures

CRYSTALBRITE DESTAIN PREMIUM 35

HYDROGEN PEROXIDE SOLUTION		30-60%
CAS number: 7722-84-1	EC number: 231-765-0	REACH registration number: 01-2119485845-22-XXXX
Classification Ox. Liq. 1 - H271 Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1A - H314 Eye Dam. 1 - H318 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) R5 O;R8 C;R35 Xn;R20/22	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove contaminated clothing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system.
Ingestion	Nausea, vomiting.
Skin contact	Burns can occur.
Eye contact	Corneal damage. Profuse watering of the eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
Specific treatments	Seek medical attention if irritation or symptoms persist. Symptomatic treatment

SECTION 5: Firefighting measures

5.1. Extinguishing media

CRYSTALBRITE DESTAIN PREMIUM 35

Suitable extinguishing media Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections See section 3,8 & 13 for further information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container. Avoid contact with oxidising agents.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

HYDROGEN PEROXIDE SOLUTION

Long-term exposure limit (8-hour TWA): WEL 1 ppm 1.4 mg/m³

Short-term exposure limit (15-minute): WEL 2 ppm 2.8 mg/m³

CRYSTALBRITE DESTAIN PREMIUM 35

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Wear a respirator fitted with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

pH 0-2

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.

10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

10.6. Hazardous decomposition products

CRYSTALBRITE DESTAIN PREMIUM 35

Hazardous decomposition products Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 1,428.57142857

Acute toxicity - inhalation

ATE inhalation (gases ppm) 12,857.14285714

ATE inhalation (vapours mg/l) 31.42857143

ATE inhalation (dusts/mists mg/l) 4.28571429

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin. May cause sensitisation by skin contact.

Eye contact Risk of serious damage to eyes.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity The product is not believed to present a hazard due to its physical nature.

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

CRYSTALBRITE DESTAIN PREMIUM 35

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	2014
UN No. (IMDG)	2014
UN No. (ICAO)	2014

14.2. UN proper shipping name

Proper shipping name (ADR/RID) HYDROGEN PEROXIDE, AQUEOUS SOLUTION

Proper shipping name (IMDG) HYDROGEN PEROXIDE, AQUEOUS SOLUTION


Proper shipping name (ICAO) HYDROGEN PEROXIDE, AQUEOUS SOLUTION

Proper shipping name (ADN) HYDROGEN PEROXIDE, AQUEOUS SOLUTION

14.3. Transport hazard class(es)

ADR/RID class	5.1
ADR/RID subsidiary risk	8
ADR/RID label	5.1 & 8
IMDG class	5.1
IMDG subsidiary risk	8
ICAO class/division	5.1
ICAO subsidiary risk	8

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-H, S-Q
Emergency Action Code	2P

CRYSTALBRITE DESTAIN PREMIUM 35

Hazard Identification Number 58
(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance CHIP for everyone HSG228.
Workplace Exposure Limits EH40.
Approved Classification and Labelling Guide (Sixth edition) L131.
Safety Data Sheets for Substances and Preparations

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 27/01/2016

Revision 7

Supersedes date 29/09/2015

SDS number CBLD5

Risk phrases in full R20/22 Harmful by inhalation and if swallowed.
R22 Harmful if swallowed.
R35 Causes severe burns.
R37 Irritating to respiratory system.
R37/38 Irritating to respiratory system and skin.
R41 Risk of serious damage to eyes.
R5 Heating may cause an explosion.
R8 Contact with combustible material may cause fire.

Hazard statements in full H271 May cause fire or explosion; strong oxidiser.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

CRYSTALBRITE DESTAIN PREMIUM 35

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.