



## Instruction Manual

### 1. To turn on the LED Emergency Light:

- 1) Turn on the master switch.
- 2) Press and hold the power button for 3 seconds and the Light will turn on.
- 3) Press the power button once and S.O.S. mode will turn on.
- 4) Press the power button once more and Strobe mode will turn on & once more to Off

### 2. To charge a device from one of the USB Output Ports for 5V 2.1A Devices:

- 1) Plug the device into one of the USB ports using the appropriate USB cable. Never force a plug into a socket. If it is the correct connection-it will fit into the socket with ease.
- 2) Turn the master switch ON.
- 3) Press the power button once. The device should show a charging symbol as when normally charging.

**Important: If need to charge two devices at the same time from two USB outputs on Juice box. Must make sure the total current of the two devices must not over 2.8A, If over 2.8A, the Juice Box will automatically shut down to protect is normal.**

**The blue light on the Juice box digital Screen will remain lit if there is a proper connection. If the blue light goes out, try again as there is no draw from device**

### 3. To charge a laptop or other device using the DC Output Port for 8.4V/ 12V / 16V / 19V Devices:

- 1) Plug the device into the Output Port using the appropriate cable/adaptor.

**Never force a plug into a socket. If it is the correct connection-it will fit into the socket with ease.**

- 2) Turn the master switch **ON**.
- 3) Press the "power" button once and 8.4V mode will be selected. "8.4V" will show in the display and the device will charge.
- 4) For 12V devices, press the "power" button once more and "12V" will appear.
- 5) For 16V devices, press the "power" button once more and "16V" will appear.
- 6) For 19V devices, press the "power" button once more and "19V" will appear.

7) The device should show a charging symbol as when normally charging.

**The blue light on the Juice box will remain lit if there is a proper connection. If the blue light goes out, try again**

#### **4. To recharge the Juice Box battery:**

**WARNING: do not charge cell phone or other device using the JB cigarette charger or wall charger. ONLY use with Juice Box as it puts out 15A...way to much for small devices**

1) Plug either the power adaptor or the 12V Cigarette lighter adaptor (supplied), into the "Input" Port for 15V 1A Recharging.

**Never force a plug into a Port. If it is correct connection- it will fit into the Port with ease.**

2) Ensure the master switch is OFF.  
3) Plug the power adaptor or 12V car adaptor into the appropriate power supply.

**The blue light on the Juice box Digital Screen will remain lit and the word "IN" will flash if there is a proper connection. If the blue light goes out, try again.**

**Recharge the battery as soon as possible after use 7-8hrs. Store the battery fully charged when possible. As a minimum, fully recharge the battery every three months.**

#### **5. Do not jumpstart a vehicle when Juice Box battery life is below 20% as it could damage the unit and void warranty.**

To jumpstart an engine (smaller than 5.0L Petrol or smaller than 3.0L Diesel):

1) Connect the black jumpstart clamp to the negative (black) terminal of the vehicle battery. Connect the red jumpstart clamp to the positive (red) terminal of the vehicle battery.  
2) Plug the jumpstart cables into the Output Port on end of of Juice Box. (under flap by light)  
4) Turn the key and start the engine.  
5) Disconnect the jump clamps.

**If vehicle does not start immediately, wait 15 seconds between starting attempts. If the vehicle does not turn over, reposition the clamps on the vehicle battery terminals to ensure proper conduction.**