



Yachtmaster Brights



FEATURES

- Double braid construction in HT Polyester
- High jacket to core ratio assisting long life
- Excellent breakload, UV and abrasion resistance
- Resistant to kinking, hocking and twisting
- Highly resistant to most chemicals
- Easy to splice
- Solid colours assist identification and aesthetic look on board
- Colour fast dye in production phase

RANGE/TECHNICAL

- 4mm - 12mm
- 100m reels
- Bulk rigger reels or cartons and larger diameters up to 40mm available on request

Solid Green, Beige or Dark Grey colour options available on request

Size (mm)	Weight kg/100m	Reel Length	BreakForce (kg)
4	1.5	100m	350
6	3.5	100m	950
8	5.3	100m	1700
10	9.0	100m	2350
12	11.2	100m	3250

APPLICATIONS

- Sheets
- Guys
- Control lines
- Out/downhauls
- Runner tails
- Traveller
- Vang
- Reefing and furling systems on cruiser/racing yachts

FIBRE CHARACTERISTICS

Fibre:Type	Description	Specific Gravity	Sensitive to	Resistant to	Heat Reaction	Strength & Elongation
Polyester	Continuous Filament	1.38	Alkalis, phenolic compounds, sulphuric acid	Most organic & mineral acids, organic solvents, bleaches & oxidising agents	Softens 228°C Melts 255°C	Equivalent wet/dry strength ratio. Elongation 35% at Break