

Epifanes Teak-O-Bello

Epifanes Teak-O-Bello is an easy to apply water-based protector for teak and other hardwoods. This unique and environmentally friendly formulation prevents the wood from weathering and discoloration for an extended period of time. Ideal for use on teak decks, teak railings, teak handrails and all other teak on board.

Type	Water based protector for teak, mahogany, iroco, bankirai and other tropical hard wood. For exterior and interior use above the waterline.
Base	Water based
Main characteristics	Fast and easy to apply Lasts longer than solvent-based teak oils and teak sealers Resists the formation of moulds. Does not affect the caulking in teak decks. Solvent free; Does not contain any VOC's and/or toxic fumes.
Colour	Brown
Density	1,010 g/cm ³
Viscosity	25 seconds Din Cup 4 mm.
Solids Content	27 ± 2 vol. %
Drying time at 20°C.	30 minutes
pH-value	8.0
Storage	Always store this product frost free and away from direct sunlight.
Surface preparation	Remove all dirt and spots by using Epifanes Teak-O-Clean & Bright or other suitable teak cleaner. Allow the wood to fully dry. Thoroughly degrease oily types of wood with Epifanes Spraythinner for Paint & Varnish or another suitable degreaser. Sand the wood to a smooth surface and degrease once more.
Application	Shake Epifanes Teak-O-Bello at least 60 seconds before use. Apply by lint-free cloth or wide brush. In general one or two treatments are sufficient. Apply thin coats only. Any film build-up must be avoided at all times. Remove stains immediately with Epifanes Teak-O-Clean & Bright or water. Remove surplus material immediately with a lint-free cloth.
Thinner	Do not thin Clean equipment with water.
Maintenance interval	Dependant on atmospheric conditions.
Theoretical coverage	7 m ² per litre
Practical coverage	Dependant on absorption power of the wood, methode of application. Loss of material due the shape of object and circumstances during application.
Recommended use	All wooden areas where for risks of slipping the application of a smooth varnish or oil finish is not suitable or desired (i.e. decks, gangways, etc.). Can also be used for treatment of teak handles, railings and other areas of exotic wood where the natural appearance of the wood is preferred and should be maintained.
Safety information	Does not contain VOC or toxic materials. Obey usual safety precautions. The use of latex gloves is recommended.