

Antifouling Thinner No.3

Thinners & Solvents

Antifouling Thinner



PRODUCT DESCRIPTION

For cleaning and thinning antifouling products. Special blend of pure solvents.

PRODUCT INFORMATION

Colour	YTA085*
Volume Solids	0%
Typical Shelf Life	2 yrs
Unit Size	500 ml 1 Lt 4 Lt 20 Lt

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Method	If directed to use this solvent for wipe down of a specific surface, use the 2-cloth method, one to apply the thinner and one to remove to avoid re-applying residues.
Hints	Ventilation and Humidity Control Ensure adequate ventilation during use.
Some Important Points	No special restrictions.
Compatibility/Substrates	Compatible with all International antifouling.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	TRANSPORTATION: Antifouling Thinner No.3 should be kept in securely closed containers during transport and storage. STORAGE: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Antifouling Thinner No.3 to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.
Safety	DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. Always use gloves and goggles and keep skin protected with overalls. Users should ensure they have a copy of the Material Safety Datasheet for this product and that they are familiar with all the safety directions before use.
IMPORTANT NOTES	<i>The technical information and suggestions for use and application presented herein are not intended to be exhaustive, but they represent the best information available to use and are believed to be reliable. They should not, however, be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses. Because this datasheet is subject to changes from time to time, it is the user's responsibility to check that this sheet is current prior to using the product.</i>

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.