

PRODUCT DESCRIPTION

A synthetic granular material. To be added into top coat paints or sprinkled onto wet paint as an aid to providing a more slip resistant finish.

- * Provides a slip resistant finish when added to or sprinkled onto paint
- * Easy application
- * Can be applied by brush, roller or spray

PRODUCT INFORMATION

Colour	YMA905
Volume Solids	100%
Unit Size	125 g 450 g

DRYING/OVERCOATING INFORMATION

Drying

Note: Touch Dry is the same as for the Finish.

Overcoating

Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

Note: Overcoating Times are the same as for the Finish.

APPLICATION AND USE

Preparation	All substrates must be clean, dry and free from contaminants.
Hints	Thinner Same as for finish. Cleaner Same as for finish. Ventilation and Humidity Control Ensure adequate ventilation during use.
Coverage	(Theoretical) - 10 m ² /lt . 8-12 m ² /lt hand broadcasting. 250-500 mls of Intergrip per 4 litres of paint when spraying/rolling.
Application Methods	Brush, Conventional Spray, Roller

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	TRANSPORTATION: Intergrip should be kept in securely closed containers during transport and storage. STORAGE: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Intergrip to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.
Safety	DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. Always use gloves and goggles and keep skin protected with overalls. Users should ensure they have a copy of the Material Safety Datasheet for this product and that they are familiar with all the safety directions before use.
IMPORTANT NOTES	<i>The technical information and suggestions for use and application presented herein are not intended to be exhaustive, but they represent the best information available to use and are believed to be reliable. They should not, however, be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses. Because this datasheet is subject to changes from time to time, it is the user's responsibility to check that this sheet is current prior to using the product.</i>

Please refer to your local representative or visit www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.