



Perfectly Maintaining Deks Olje D1 treated surfaces in harsh UV and monsoonal conditions

Deks Olje® D1 represents one of the most natural and beautiful quality wood finishes available in the market.

When however permanently exposed to monsoonal conditions such as regular rain and high UV conditions, it will start to gradually lighten over time.

This gradual lightening into a silverfish light grey colour does NOT mean that the wood loses its protection.

Whilst Deks Olje® D1 belongs into the wood and should always have been applied with at least 3 applications to fully penetrate and saturate the wood, it will continue to protect the wood from deep inside.

DEKS OLJE® D.1 when gradually lightening over time due to the effects of the sun and UV rays affecting the top surface, can easily be rejuvenated by considering a maintenance coat application.

The following steps are advised:

Clean the surface with NET-TROL®* to remove potential traces of grime or slightly sand the surface with a 220 grit sandpaper.

Apply one or two DEKS OLJE® D.1 maintenance coats to saturate the top wood layer again and to restore the finish.

The maintenance coat best is applied with a soft clean rag fully soaked with Deks Olje® D1 and rung out so that it is damp to the touch and replenish the top surface layer.

Wipe over the surface with the soaked rag, rub the product into the wood to saturate the top wood layers avoiding any puddled material and glossy patches on the wood.

Resoak the rag in case it is getting too dry and continue with the maintenance coat.

Usually 1 or 2 maintenance applications will be sufficient. Let dry and your good again.

OWATROL – The Easiest And Most Efficient Maintenance System Around

Page 1 of 1

Deks Olje D1 Maintenance Application
Owatrol Asia-Pacific / Huehn & Partners
contact@deksolje.com.au