SUPERSUB SMART

THE ORIGINAL, AWARD-WINNING, LOW PROFILE, NARROW, AUTOMATIC ELECTRIC BILGE PUMP PROVEN OVER 20 YEARS

- No separate bilge switch required
- ▶ Low profile design is ideal for narrow bilge
- ▶ Retrofittable with angled mounting bracket to aid installation
- Low power consumption
- Suitable for use in fresh and saltwater
- ▶ Integrated bleed ball prevents air locks

	Supersub Smart			
Model	Supersub Smart 650 (with non return valve)	Supersub Smart 1100 (with non return valve)	Supersub Smart 1100 (with non return valve)	
PART NUMBER	SS5212	SS1212	SS1224	
Weight	0.3kg (0.7lbs)	0.5kg (1.0lbs)	0.5kg (1.0lbs)	
Voltage	12V d.c.	12V d.c.	24V d.c.	
Fuse size	5 amps	5 amps	2.5 amps	
Cable size	1.5mm² (16AWG)			
Hose connection	19mm (¾") / 25mm (1") stepped port	25mm (1") / 28mm (11/8") stepped port	25mm (1") / 28mm (1½") stepped port	
Materials	Pump Body: Polypropylene, High Temperature ABS, Fully Potted Circuitry. Locking Ring: Acetal, Impeller: Glass-Filled PBT, Seals: Nitrile, Fasteners: Stainless Steel			
Materials in contact with fluid	Polypropylene, ABS, Glass-Filled PBT, Nitrile			

	Performance Performance		
PART NUMBER	SS5212	SS1212	SS1224
Max discharge head		3m (10ft)	
Open flow rate	40 ltrs/min (650 US GPH)	66 Itrs/min (1050 US GPH)	
Open flow rate at 1m (3ft) head	34 Itrs/min (550 US GPH)	47 ltrs/min (750 US GPH)	

For further guidance on the selection of the correct pump, please see page 117


WARRANTY 3 YEARS


- CE Certified
- ISO 8849
- ISO 15083
- ISO 8846
- ISO 10133
- ABYC H-22
























FRONT VIEW

SUPERSUB

DESIGNED TO FIT IN NARROW BILGE SPACES WHERE OTHERS DO NOT REACH

- ▶ Easy installation outlet and pump body rotate to suit your installation
- ▶ Easy maintenance with unique easy clean strainer
- ▶ Efficient operation low power consumption
- Low profile strainer leaves bilge almost dry
- ▶ Integrated bleed ball prevents air locks

	Supersub			
MODEL	Supersub 500	Supersub 650 (with non return valve)	Supersub 1100 (with non return valve)	Supersub 1100 (with non return valve)
PART NUMBER	SS5012	SS5022	SS1012	SS1024
Weight	0.27kg (0.6lbs)		0.4kg (0.9lbs)	
Voltage	12V d.c. 24V d.c.			24V d.c.
Fuse size	5 amps 2.5 amps			2.5 amps
Cable size	1.5mm² (16AWG)			
Hose connection	19mm (¾")	1 (34") 19mm (34") / 25mm (1") 25mm (1") / 28mm (11%") stepped port stepped port		
Materia s	Pump Body: Polypropylene, High Temperature ABS, Fully Potted Circuitry. Locking Ring: Acetal, Impeller: Glass-Filled PBT, Polypropylene, Seals: Nitrile, Fasteners: Stainless Steel			
Materials in contact with fluid	Polypropylene, ABS, Glass-Filled PBT, Nitrile			
Accessories	Electric bilge switches BE9003 and BE9006, for all bilge accessories see page 38-40, Non return valve LV1219			

	Performance		
PART NUMBER	SS5012	SS5022	SS1012 / SS1024
Max discharge head		3m (10ft)	
Open flow rate	32 Itrs/min (500 US GPH)	40 Itrs/min (650 US GPH)	66 Itrs/min (1050 US GPH)
Open flow rate at 1m (3ft) head	25 Itrs/min (400 US GPH)	34 ltrs/min (550 US GPH)	47 Itrs/min (750 US GPH)

For further guidance on the selection of the correct pump, please see page 117