

3-in-1 Game Chair Assembly Instructions



Contents

- 16 3/16" Hex head bolts
- 16 Threaded inserts (Phillips head tip)
- 4 wood dowels
- Wood Pieces shown in last product photo

*** You will need a 3/16" Allen wrench and may need a Phillips head screwdriver for assembly ***

1. Start with one side laid down on a clean soft surface. When installing the wood components, it is easiest to have the front of the chair side pointing to the ceiling.
2. Insert 1 wood dowel into the top hole of the chair top. This hole is larger in diameter and not drilled fully through the wood.
3. Insert a bolt through the middle hole of the side.
4. Insert a threaded insert into each of the insert holes of the BACK PIECE. These holes are larger in diameter and are not drilled fully through the wood. The Insert internal threads should face the bolt hole so that a bolt can engage with the threads.
5. Using a 3/16" Allen wrench, join the BACK PIECE to the side where you inserted the bolt from step 3. Screw the bolt into the insert **just enough** to engage the insert threads. You may need to use a Phillips head screwdriver to adjust the orientation of the insert so the bolt can engage the threads. Do not tighten the pieces together, you will tighten everything up later after the seat is in place.
6. Repeat Step 3 and 4 for the remaining top and front pieces. Then repeat from Step 2 with the other chair side until all pieces are loosely connected, except for the seat. The chair should be able to stand at this point.
7. Install the seat into its place and tighten all bolts surrounding the seat, locking the seat in place.
8. Tighten the top support bolts. All bolts should be tight at this point.
9. Finally, add the leg pads to the bottom of the legs and the installation is complete.