

DESCRIPTION

Living EarthTM Primer is used in conjunction with Living EarthTM Water-Based Stain. It was created for substrates that are excessively porous. Some concrete, particularly those finished poorly (not closed with a steel trowel), broomed, or very old concrete, may absorb Living EarthTM Water-Based Stain so deeply that little color, if any, is visible. Living EarthTM Primer reduces the porosity helping the color to reach full development. Living EarthTM Primer is clear and will leave no color when dry. Living EarthTM Primer may be used across an entire project if excessive porosity is apparent. It may also be used on isolated areas that are “open.”

LIMITATIONS

Under extreme circumstances of excessive porosity, Living EarthTM Primer may not satisfactorily resolve coloration complications. For use by trained professionals that have read and understand the complete TDS and SDS.

PACKAGING

Living EarthTM Primer is available in one-gallon (3.785 L) sizes.

COVERAGE

Coverage will vary widely due to porosity. One-gallon (3.785 L) of Living EarthTM Primer will cover approximately 200-300 square feet of concrete surface depending on application technique and/or surface conditions.

STORAGE

Store in a safe place, out of direct sunlight. Keep containers tightly sealed. DO NOT allow product to freeze. Shelf life is approximately 12 months. Storage must be under roof and off the floor. Rotate inventory to maintain product that is within limits.

SURFACE PREPARATION

Concrete Coatings, Inc. strongly recommends representative jobsite samples (mock-ups should always be prepared on the same concrete as the stain is to be applied to.) Individuals who will be performing the work should test different sections of the concrete to determine suitability, coverage of the stain and final appearance

Surface preparation for application of Living EarthTM Primer will be the same as for Living EarthTM Water-Based Stain.

CAUTION

KEEP OUT OF REACH OF CHILDREN. **Inhalation:** Avoid prolonged breathing of airborne dust, particularly present during mixing. Use NIOSH approved respirator for nuisance if threshold limit values are unsafe. **Skin Contact:** Skin contact may cause irritation. Remove contaminated clothing and wash affected skin with soap and water. Launder clothing before reuse. If symptoms persist, seek medical attention. **Eyes:** Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 minutes. If symptoms persist, seek medical attention.

APPLICATION

MASK: Mask all areas requiring protection. Be certain to mask to an ample height, especially if spraying.

Spraying:

1. Apply Living EarthTM Primer with a pump-up sprayer in a fine mist. A light coat is preferred, as heavy applications will affect color and create an artificial shine or gloss.
2. On substrates that have isolated areas of high porosity, Living EarthTM Primer may be “feathered” or “faded” with pump-up sprayer. Apply the more concentrated spray on “open”, porous areas and “feather” spray to nothing in tight-troweled areas.
3. Allow Living EarthTM Primer to dry to the touch, then proceed with Living EarthTM Water-Based Stain

CLEAN UP

Living EarthTM Primer can be cleaned up with water. Discard brush or application utensils in an appropriate manner.

TEMPERATURE/CURE

Typically apply when surface and ambient temperatures range between 50°F (10°C) and 90°F (32°C) and will remain that way for 24 hours.

DISPOSAL

Contact your local government household hazardous waste Coordinator for information on disposal of unused product.

KEEP OUT OF REACH OF CHILDREN

ORDER SPECIFICATION

Product: Living Earth TM Primer		
Shipping Weight: 10lbs (4.5kg)	Container Size: 1 Gallon (3.79L)	Item Number: WS-PRIME

“Concrete Coatings Inc. warrants its products to be free of manufacturing defects and that they will meet Concrete Coatings Inc. current published physical properties when applied in accordance with Concrete Coatings Inc. written directions and tested in accordance with ACI, ASTM and Concrete Coatings Inc. Standards. There are no other warranties by Concrete Coatings Inc. of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Concrete Coatings Inc. shall not be liable for damages of any sort, including remote or consequential damages, resulting from any claimed breach of any warranty, whether expressed or implied, from any other cause whatsoever. Concrete Coatings Inc. will not be responsible for use of this product in a manner to infringe on any patent held by others. User assumes all liability and risk associated with use, selection, application and warranty of product. Concrete Coatings Inc. makes no representation as to the suitability of product for any application and/or damages of any kind directly or indirectly associated with its selection or application.”

FOR THE LOCATION OF YOUR NEAREST CONCRETE COATINGS INC. REPRESENTATIVE, CALL NATIONWIDE TOLL-FREE 1-800-443-2871