



Liquid Release

For concrete texturing mats

PRODUCT DESCRIPTION: TRU IMPRESSIONS Release Liquid is a specially formulated colorless bond breaker designed to prevent freshly placed concrete from adhering to texturing mats.

Tru Impressions Release Liquid forms a lubricating barrier that prevents sticking, concrete build up, and friction between the texturing mats and the green concrete. Tru Impressions Release Liquid is used on plain or integrally pigmented concrete and in combination with Tru Impressions Dust On Color Hardener.

BENEFITS: EXCELLENT RELEASE CHARACTERISTICS... ALLOWS MONOTONE STAMPING (CLEAR) OPTION... ALLOWS RELEASE IN AREAS WHERE POWDERS CANNOT BE USED WITH LESS RESULTING CLEAN-UP OR MESS...EASY TO USE.

COMPOSITION: Proprietary blend of slow drying hydrocarbon based solvents and surface acting chemicals

PHYSICAL PROPERTIES at	APPROXIMATE VALUES:
Weight per Gallon:	6.55 +/- 0.1 lb./ gallon
Color:	Light yellow clear liquid
Viscosity-Brookfield:	5 cps
Flash Point:	150° F (65.5°C)
V.O.C. Content:	445 g/L (3.71 lb./ gallon) per EPA Method 24*

***VOC COMPLIANCE:** Tru Impressions Release Liquid contains less than 450 g/L (3.75 lb. /gal.) volatile organic compounds. Meets Architectural Coatings Section 183(e) Final Rule Limit for release agents for most states, excluding California and New Jersey.

DIRECTIONS FOR USE: Place, vibrate and float the concrete surface according to standard ACI recommendations. Cover or protect adjacent surfaces. Following the initial floating, when excess moisture is no longer evident, apply Release Liquid liberally to the texture mats and to the concrete using a garden type sprayer. To avoid evaporation of the material, apply Release Liquid only in the area where the next few mats are to be placed. One gallon of Tru Impressions Release Liquid will be sufficient for approximately 150 square feet of concrete surface. Immediately begin the texturing application. Do not trowel or mix Release Liquid into the plastic concrete surface. To make corrections on the plastic concrete surface, use the texturing tool to press out unwanted impressions. Upon completion of the stamping process, clean texturing mats using plain water. After seven days, seal the textured concrete surface with Tru Impressions Stampsheen for a high gloss finish.

CAUTIONS: Use Tru Impressions Release Liquid only on the immediate area to be imprinted. Do not trowel or mix Release Liquid into plastic concrete. Avoid inhalation of vapors or mist. Avoid contact with skin and eyes. Use only with adequate ventilation. Wear protective clothing, respirator and safety goggles during handling and placement.

WARNINGS: Tru Impressions Release Liquid is a COMBUSTIBLE LIQUID! Wear protective clothing and safety glasses during application. Do not apply Release Liquid in or around buildings occupied by non-construction personnel, as the solvent odors may be irritating. Use with adequate ventilation. Avoid breathing vapors. People with medical conditions, or who are pregnant should not be exposed to vapors or fumes. All HVAC openings, windows and air intakes should be closed during exterior applications as well to prevent intake of fumes into the building interior. Tru Impressions Release Liquid is not to be applied in or near areas containing food products. These should be removed and only returned after all solvent vapors have dissipated. For compliance with AIM Clean Air Act regulations, thinning of this product is not allowed. Make sure that the application is static free. Keep Release Liquid away from sparks, open flame, and

sources of ignition. Store away from heat. Avoid ingestion, skin and eye contact and inhalation of the spray mist.

WARNINGS (Continued): Keep away from food and drink. Do not take internally. Protect all grass, foliage and related landscaping from contact with Release Liquid. Use with OSHA/NIOSH approved eye protection and air respirator. Empty container may contain explosive vapors that are heavier than air. Keep container closed. Do not cut or weld on or near empty container. Refer to product M.S.D.S. (Material Safety Data Sheet) for further health and safety information. FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. For medical emergencies only, call Chemtrec at 1-800-424-9300.

H.M.I.S. CODES: HEALTH = 2, FLAMMABILITY= 2, REACTIVITY = 0, P.PROTECTION. = G

SHIPPING NAMES: Petroleum Naphtha, Combustible Liquid N.O.S., Hazard Class 8, NA 1993, Packing Group III

SHIPPING CLASS: ITEM 155250, SUB 2, LTL 65 - Concrete Release Agent

PACKAGING: 5-gallon (18.9 L) pails, 55 gallon (207.9 L) drums

STORAGE: 40 to 90° F.

SHELF LIFE: 1-2 years properly stored

LIMITED WARRANTY: This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.