



ACCENT RELEASE

COLORED STAMPING TOOL BONDBREAKER

PRODUCT DESCRIPTION

Tru Impressions Accent Release Agent is a UV stable, pigmented powder designed to prevent freshly placed concrete from adhering to concrete texturing mats. Accent Release transfers the details of concrete texturing mats to freshly placed concrete in matching or contrasting colors. Accent release provides the “antique” look commonly seen with stamped concrete. Accent Release is used on plain or integrally pigmented concrete and in combination with Tru Impressions dust on colored hardener. Several colors may be used together to produce more of a unique, custom result. Typical uses include: stamped concrete and overlay, floors, sidewalks, decks, and driveways.

COVERAGE

Approximate coverage rate is 3 pounds per 100 square feet. The amount of accent release agent used depends upon the desired depth of the texturing mat impression and the degree to which the concrete has set.

APPLICATION

Place, screed and float the concrete surface as required. Apply Tru Impressions color hardener as specified in the product data sheet. When excess moisture is no longer evident and it is time to texture, broadcast Tru Impressions accent release in a thin uniform layer over the concrete surface to be textured. When using more than one pail, material should be mixed together especially when from different batch numbers. A Release Brush is a very effective way to disperse the powder uniformly. Material should be “fluffed” up by hand before use as it often settles over time. The brush is coated with the release and flung onto the surface and allowed to settle. Texture mats should may be placed immediately following the accent release application. Release should not be applied to areas that will not be stamped within 20 minutes to prevent areas of moisture break thru which can result in irregular stamping and sticking of surface material. Removal of the excessive release can take place after the concrete is sufficiently set and the surface can not be damaged-Usually 24 hours. Excess material may be swept from the surface and residual accent release may be removed by using allow setting pressure washer or light scrubbing(Care must be taken to not remove surface concrete) . After the concrete is cleaned and dry, apply a clear, non-yellowing acrylic sealer such as Walttools Stampsheen to protect and enhance the newly placed textured concrete.

CAUTIONS

KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Material Safety Data Sheet and Warranty. **DO NOT TAKE INTERNALLY.** Avoid contact with skin and eye. Use only with adequate ventilation and use a NIOSH respirator when exposure levels are above applicable limits. **LIMITED WARRANTY:** This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.

Walttools 1246 Leah Rd Morris, IL 60450
888-263-5895

walttools.com

