# SAFETY DATA SHEET

### 1. Identification

Product number Product identifier Revision date Company information	1000010088 <b>19 OZ VISION GLASS CLEANER LB 12PK</b> 09-20-2015 BROTHERS NAMCO MFG 10900 60TH STREET NORTH GRANT, MN 55082 United States
Company phone	General Assistance 651-646-1696
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	02
Supersedes date	07-17-2015
Recommended use	Cleaner
Recommended restrictions	None known.

### 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Not classified.	
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Extremely flammable aerosol.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	Wash hands after handling.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

### 3. Composition/information on ingredients

/lixtures			
Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Isopropyl Alcohol		67-63-0	2.5 - 10
Butane		106-97-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below reportable le	vels		90 - 100

Other components below reportable levels

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	

#### Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media Contents under pressure. Pressurized container may explode when exposed to heat or flame. Specific hazards arising from During fire, gases hazardous to health may be formed. the chemical Firefighters must use standard protective equipment including flame retardant coat, helmet with Special protective equipment and precautions for firefighters face shield, gloves, rubber boots, and in enclosed spaces, SCBA. **Fire-fighting** Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose equipment/instructions holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. General fire hazards Extremely flammable aerosol.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment.

Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
		50 ppm
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3
		400 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Limit	Values	
Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
US. NIOSH: Pocket Guide to	o Chemical Hazards	
Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3
	TWA	5 ppm
	TWA TWA	
111-76-2)		5 ppm
111-76-2)		5 ppm 1900 mg/m3
111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS	TWA	5 ppm 1900 mg/m3 800 ppm
111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS	TWA	5 ppm 1900 mg/m3 800 ppm 1225 mg/m3
111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS	TWA STEL	5 ppm 1900 mg/m3 800 ppm 1225 mg/m3 500 ppm
111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS	TWA STEL	5 ppm 1900 mg/m3 800 ppm 1225 mg/m3 500 ppm 980 mg/m3 400 ppm
111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0)	TWA STEL TWA	5 ppm 1900 mg/m3 800 ppm 1225 mg/m3 500 ppm 980 mg/m3
111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0)	TWA STEL TWA	5 ppm 1900 mg/m3 800 ppm 1225 mg/m3 500 ppm 980 mg/m3 400 ppm 1800 mg/m3
111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0) Propane (CAS 74-98-6)	TWA STEL TWA TWA	5 ppm 1900 mg/m3 800 ppm 1225 mg/m3 500 ppm 980 mg/m3 400 ppm 1800 mg/m3

			-		
2-Butoxyethanol (CAS	200 mg/g	Butoxyacetic	Creatinine in	*	
111-76-2)		acid (BAA), with hydrolysis	urine		
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*	

\* - For sampling details, please see the source document.

#### **Exposure guidelines**

#### US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) US - Minnesota Haz Subs: Skin designation applies	Can be absorbed through the skin.
2-Butoxyethanol (CAS 111-76-2) US - Tennesse OELs: Skin designation	Skin designation applies.
2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.

US NIOSH Pocket Guide to C	hemical Hazards: Skin design	ation
2-Butoxyethanol (CAS 11	1-76-2)	Can be absorbed through the skin.
US. OSHA Table Z-1 Limits for	or Air Contaminants (29 CFR 1	910.1000)
2-Butoxyethanol (CAS 11	1-76-2)	Can be absorbed through the skin.
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
Individual protection measures,	such as personal protective ec	uipment
Eye/face protection	Wear safety glasses with side s	hields (or goggles).
Hand protection	Wear appropriate chemical resi	stant gloves.
Skin protection		
Other	Wear suitable protective clothin	g.
Respiratory protection	If permissible levels are exceed air-supplied respirator.	ed use NIOSH mechanical filter / organic vapor cartridge or an
Thermal hazards	Wear appropriate thermal prote	ctive clothing, when necessary.
General hygiene considerations		ays observe good personal hygiene measures, such as washing before eating, drinking, and/or smoking. Routinely wash work ent to remove contaminants.

## 9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	-156.0 °F (-104.4 °C) propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	23.01 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
	Not available.

Other information Specific gravity

0.977 estimated

10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Fire or intense heat may cause violent rupture of packages.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

### 11. Toxicological information

### Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

Acute toxicity	Expected to be a low hazard for us	sual industrial or commercial handling by trained personnel.
Components	Species	Test Results
2-Butoxyethanol (CAS 111-7	6-2)	
Acute		
Dermal		
LD50	Guinea pig	230 ml/kg, 24 Hours
		7.3 ml/kg, 4 Days
	Rabbit	450 ml/kg, 24 Hours
		435 mg/kg, 24 Hours
		0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1200 mg/kg
	Rat	530 - 2800 mg/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes

Components	Species	Test Results
	Rat	1355 mg/l
Isopropyl Alcohol (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	16.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	> 10000 ppm, 6 Hours
Oral		
LD50	Rat	5.84 g/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
* Estimates for product may I	be based on additional component data not show	٦.
Skin corrosion/irritation	Not applicable. Prolonged skin contact may ca	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sen	sitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinog	en by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall	Evaluation of Carcinogenicity	
2-Butoxyethanol (CAS 1 OSHA Specifically Regulat	11-76-2) 3 Not classifiat ed Substances (29 CFR 1910.1001-1050)	ble as to carcinogenicity to humans.
Not listed.		
Reproductive toxicity	This product is not expected to cause reproduce	ctive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard. Not likely, due to the	form of the product.
Chronic effects	Prolonged inhalation may be harmful. May be	harmful if absorbed through skin.
	2-Butoxy ethanol may be absorbed through the prolonged. These effects have not been observed and the prolonged.	e skin in toxic amounts if contact is repeated and rved in humans.

### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

11-76-2)		
LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
67-63-0)		
IC50	Algae	1000.0001 mg/L, 72 Hours
	LC50 67-63-0)	LC50 Inland silverside (Menidia beryllina) 67-63-0)

Components		Species	Test Results	
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours	
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours	
* Estimates for product may	be based on	additional component data not shown.		
Persistence and degradability	No data is	available on the degradability of this proc	duct.	
Bioaccumulative potential	No data a	vailable.		
Partition coefficient n-octa	nol / water (l	og Kow)		
2-Butoxyethanol		0.83		
Butane		2.89		
Isopropyl Alcohol		0.05		
Propane		2.36		
Mobility in soil	No data available.			
Other adverse effects		adverse environmental effects (e.g. ozone endocrine disruption, global warming pote		
13. Disposal consideration	ons			
Disposal instructions	Collect an	d reclaim or dispose in sealed containers	at licensed waste disposal site. Contents	

	under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

DOT

ונ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### ΙΑΤΑ

~		
UN number	UN1950	
UN proper shipping name	Aerosols, flammable	
Transport hazard class(es)		
Class	2.1	
Subsidiary risk	-	
Label(s)	2.1	
Packing group	Not applicable.	
Environmental hazards	No.	
ERG Code	10L	

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and the IBC Code	

DOT





### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4) Not listed.
SARA 304 Emergency release notification Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - No Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

### Safe Drinking Water Act Not regulated.

(SDWA)

### **US state regulations**

### US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0) Propane (CAS 74-98-6)

### US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0) Propane (CAS 74-98-6)

### US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0) Propane (CAS 74-98-6)

### US. Rhode Island RTK

Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0) Propane (CAS 74-98-6)

### US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

#### United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	07-17-2015
Revision date	09-20-2015
Version #	02
Disclaimer	We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Alternate Trade Names