



MADACO SAFETY PRODUCTS, INC.

1313 N GRAND AVE #249 WALNUT CA 91789 (909) 614-1756

Product Specifications



- TB-205A-16 (Combo F):**
- **Harness**
 - 5 pt. adjustment
 - Lightweight
 - Heavy duty leg/chest straps
 - 5,000Lbs rated heavy duty nylon webbing
 - Lanyard Latch ring
 - Size: M- 2XL (Universal) Also available in oversized and extra padding
 - Plated hardware for corrosion resistance
 - Forged hardware parts
 - 1 Adjustable back D-ring for fall protection and restraint purpose
 - Insertion buckles at chest and legs
 - Buckles on the side for vertical adjustments
 - Attached 6' lanyard with internal shock pack

DESCRIPTION	RATED TENSILE STRENGTH
1 ¾" BLACK NYLON WEBBING	5,000 LBS
1 ¾" ALLOY STEEL INSERTION BUCKLE	4,000 LBS
STEEL D-RING	5,000 LBS
PLASTIC LANYARD/ELASTIC KEEPER	N/A
Meets or exceeds applicable OSHA and ANSI standards, including ANSI Z359.1	

Testing References:

- Webbing: ANSI Z359 3.2.2.2 – 3.2.2.7
- D-rings: ANSI Z359 3.2.1.5 and 3.2.1.7
- Buckles: ANSI Z359 3.2.1.6
- Harness: ANSI Z359 3.2.2.7
- Testing Procedure: ANSI Z359 4.3.3.1 and 4.3.3.2
- Performance Rating: 5,000lbs Static Load

OSHA requires that the employer shall provide a training program for each employee who might be exposed to fall hazards. As part of the training program, the user of this product must:

- Become familiar with all instructions contained in the product manual
- Be trained in the correct use and care of their equipment
- Be aware of its application limitations
- Know and understand the consequences of improper use
- FAILURE TO FOLLOW INSTRUCTIONS MAY RESULT IN SERIOUS INJURY OR DEATH