



1313 N GRAND AVE #249 WALNUT CA 91789 (909)614-1756

Product Specifications



RK-30-1036:

- Universal 3 PT adjustable harness (TB-201A)
- 30 ' of 5/8" Polydac rope rated at over 23Kn (5,000 lbs) (L-RG30S)
- 2 gallon re-usable storage bucket
- Shock pack that extends 42" and absorbs the impact of a fall
- Multiple use roof anchor
- Carbon steel and plated 5/8" rope grab
- Forged and plated double locking snap hook rated at over 23Kn (5,000 Lbs)
- Forged and plated modified D shaped auto locking carabiner rated at over 23Kn (5,000 Lbs)

DESCRIPTION	RATED TENSILE STRENGTH
1 3/4" TAN AND ORANGE NYLON WEBBING	5,000 LBS
1 3/4" PLATED INSERTION STYLE BUCKLE	4,000 LBS
STEEL D-RING	5,000 LBS
PLASTIC LANYARD/ELASTIC KEEPER	N/A
MULTIPLE USE ROOF ANCHOR	5,000 LBS
SHOCK PACK	450 LBS START TO EXPAND
CARABINER	5,000 LBS
ROPE GRAB	5,000 LBS
Meets or exceeds applicable OSHA and ANSI standards, including ANSI Z359.1	

Testing References:

- Webbing: ANSI Z359 3.2.2.2 – 3.2.2.7
- D-rings: ANSI Z359 3.2.1.5 and 3.2.1.7
- Buckles: ANSI Z359 3.2.1.6
- Harness: ANSI Z359 3.2.2.7
- Testing Procedure: ANSI Z359 4.3.3.1 and 4.3.3.2
- Performance Rating: 5,000lbs Static Load

OSHA requires that the employer shall provide a training program for each employee who might be exposed to fall hazards. As part of the training program, the user of this product must:

- Become familiar with all instructions contained in the product manual
- Be trained in the correct use and care of their equipment
- Be aware of its application limitations
- Know and understand the consequences of improper use
- FAILURE TO FOLLOW INSTRUCTIONS MAY RESULT IN SERIOUS INJURY OR DEATH