

## 1313 N GRAND AVE #249 WALNUT CA 91789 (909)614-1756

## **Product Specifications**



## **TB-205A-MAX-16-DUFF:**

- 5 Pt adjustability
- Light weight harness
- Heavy duty leg/chest straps
- 7,000 Lbs rated heavy duty nylon/ polyester webbing
- Size: M L (Universal) Also available in oversize and extra padding
- Plated hardware for corrosion resistance
- Forged hardware parts
- 1 back D-ring for fall protection and restraint purpose
- X-Pad on the back
- Leg pads
- Quick release buckles at chest and legs
- 6' fall arrest lanyard with HS Hooks



DECORPORA	DATED TENSUE STRENGTU
DESCRIPTION	RATED TENSILE STRENGTH
1 ¾" GREY AND ORANGE WEBBING	7,000 LBS
1 ¾" ALLOY STEEL INSERTION BUCKLE	4,000 LBS
STEEL D-RING	5,000 LBS
PLASTIC LANYARD/ELASTIC KEEPER	N/A
Meets or exceeds applicable OSHA and ANSI standards, including ANSI Z359.1	

**Testing References:** 

Webbing: ANSI Z359 3.2.2.2 – 3.2.2.7 D-rings: ANSI Z359 3.2.1.5 and 3.2.1.7

Buckles: ANSI Z359 3.2.1.6 Harness: ANSI Z359 3.2.2.7

Testing Procedure: ANSI Z359 4.3.3.1 and 4.3.3.2

Performance Rating: 5,000lbs Static Load

OSHA requires that the employer shall provide a training program for each employee who might be exposed to fall hazards. As part of the training program, the user of this product must:

- Become familiar with all instructions contained in the product manual
- Be trained in the correct use and care of their equipment
- Be aware of its application limitations
- Know and understand the consequences of improper use
- FAILURE TO FOLLOW INSTRUCTIONS MAY RESULT IN SERIOUS INJURY OR DEATH