

Features/Benefits

- Incredibly durable and low maintenance
- Technology enhanced bond, seam and ar strength
- Heavy duty! 13x stronger than industry standards
- Thermal comfort - remains cool to the touch, even in sunlight
- Incredibly soft, supple and luxurious
- Inherently stain resistant and stays looking its best

Earth Friendly

- **Greenguard® Certified**
- No PVC (Polyvinyl Chloride)
- No POPs (Persistent Organic Pollutants)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No HFRs (Halogenated Flame Retardants)
- Meets the most stringent VOC standards
- No Plasticizers, Heavy Metals, Stabilizers, Phthalates or Bisphenol A (BPA)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

Maintenance & Care Instructions

Keep Ultrafabrics, LLC brand surfaces looking great by routine and proper maintenance. Follow these guidelines to extend the life of the fabric:

- Clean regularly with soap and water
- Wipe up spills as soon as they occur
- Remove stains with alcohol-based cleaners like Fantastik® and Formula 409®
- Clean/disinfect using a 5:1 water/bleach solution
- Thoroughly rinse all solution residue with clean water
- Air dry



SPECIFICATIONS

COMPOSITION:	100% POLYURETHANE SURFACE 100% REINFORCED RAYON BACKING
WEIGHT:	APPROX. 9.7 OZ. PER SQUARE YARD (APPROX. 330 GRAMS PER SQUARE METRE)
	APPROX. 14.6 OZ. PER LINEAR YARD (APPROX. 450 GRAMS PER LINEAR METRE)
THICKNESS:	APPROX. 0.95 MILLIMETRES
WIDTH:	54 INCHES / 137 CENTIMETRES
PUT-UP:	APPROX. 33 YDS / 30 METRES R.O.T.

PERFORMANCE PROPERTIES:

STANDARD:

ABRASION:	ASTM D 4157 / 400,000 DOUBLE RUBS (WYZENBEEK)* BS 2543 / 180,000 RUBS (MARTINDALE)* <small>*MEETS OR EXCEEDS</small>
DIMENSIONAL CHANGE:	ASTM D 3597
HYDROLYSIS:	ASTM D3690-02 SECT. 6.11 (HYDROLYTIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)
SEAM STRENGTH:	ASTM D 751
STRETCH & SET:	SAE J855
TEAR STRENGTH:	ASTM D 1117
TENSILE STRENGTH:	ASTM D 1117

COLORFASTNESS:

CROCKING:	AATCC 8, CLASS 5 WET & DRY
LIGHT:	AATCC 16E, AATCC 16A, CLASS 5 ISO 105 - B02 : 1999 GRADE 7/8
GAS:	AATCC 23, CLASS 5
OZONE:	AATCC 109, CLASS 5

F/R RATING:

ASTM E 84 (ADHERED)	CLASS A
CA 117 E	CLASS 1
FMVSS 302 & 95/28 ANNEX IV	PASS
NFPA 260	CLASS 1
UFAC	CLASS 1

PLEASE NOTE:

THESE FABRICS, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAVE BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF:

- FAR SPECIFICATIONS
- IMO A.652 (16)
- ASTM E 84 (UNADHERED)
- BS 5852 PT 0, 1 & 5 (CRIB 5)
- CALIFORNIA TECHNICAL BULLETIN 133
- BS 5867 PART 2 TYPE B
- NFPA 701
- BS 7175

