




Blanking Plug for Tube Ends Type FI-VSK ▪ Series L / S



Series	Tube OD [mm]	PN [bar]	Dimensions [mm]						Weight [kg] ca. per 100 ²	Ordering Codes	
			L	L1 ¹	L2	S1	S2	Blanking plug supplied with cutting ring & union nut		Blanking plug only	
L	6	500	14	22	7	12	14	2,6	FI-VSK-06L-W3-MS	FI-VSK-06L-W3	
	8	500	15	23	8	14	17	3,8	FI-VSK-08L-W3-MS	FI-VSK-08L-W3	
	10	500	16	24	9	17	19	4,8	FI-VSK-10L-W3-MS	FI-VSK-10L-W3	
	12	400	17	25	10	19	22	6,5	FI-VSK-12L-W3-MS	FI-VSK-12L-W3	
	15	400	18	26	11	24	27	9,8	FI-VSK-15L-W3-MS	FI-VSK-15L-W3	
	18	400	19	28	11,5	27	32	13,9	FI-VSK-18L-W3-MS	FI-VSK-18L-W3	
	22	250	21	30	13,5	32	36	19,3	FI-VSK-22L-W3-MS	FI-VSK-22L-W3	
	28	250	22	31	14,5	41	41	31,0	FI-VSK-28L-W3-MS	FI-VSK-28L-W3	
	35	250	25	36	14,5	46	50	48,7	FI-VSK-35L-W3-MS	FI-VSK-35L-W3	
42	250	27	39	16	55	60	62,1	FI-VSK-42L-W3-MS	FI-VSK-42L-W3		
S	6	800	18	26	11	14	17	4,0	FI-VSK-06S-W3-MS	FI-VSK-06S-W3	
	8	800	20	28	13	17	19	4,6	FI-VSK-08S-W3-MS	FI-VSK-08S-W3	
	10	800	20	29	12,5	19	22	6,9	FI-VSK-10S-W3-MS	FI-VSK-10S-W3	
	12	630	22	31	14,5	22	24	8,7	FI-VSK-12S-W3-MS	FI-VSK-12S-W3	
	14	630	24	34	16	24	27	12,0	FI-VSK-14S-W3-MS	FI-VSK-14S-W3	
	16	630	24	34	15,5	27	30	15,1	FI-VSK-16S-W3-MS	FI-VSK-16S-W3	
	20	400	28	39	17,5	32	36	24,6	FI-VSK-20S-W3-MS	FI-VSK-20S-W3	
	25	400	32	44	20	41	46	43,9	FI-VSK-25S-W3-MS	FI-VSK-25S-W3	
30	400	34	47	20,5	46	50	55,1	FI-VSK-30S-W3-MS	FI-VSK-30S-W3		
38	400	39	54	23	55	60	84,4	FI-VSK-38S-W3-MS	FI-VSK-38S-W3		

¹ Approximate dimension with nut tightened.

² Weight including cutting ring and union nut.