


## Straight Fitting with 24° Taper / O-Ring (DKO)

### Type FI-SNV ▪ Series L / S



Series	Tube OD	PN	Dimensions				Weight	Ordering Codes
	[mm]		[bar]	[mm]				
	D1		D2	L1	L2	S1	per 100	Fitting body only
<b>L</b>	6	500	3	34	36,7	14	3,2	<b>FI-SNV-06L-B-W3-DKO</b>
	8	500	5	34	36,7	17	4,6	<b>FI-SNV-08L-B-W3-DKO</b>
	10	500	6	36	37,8	19	6,3	<b>FI-SNV-10L-B-W3-DKO</b>
	12	400	8	36	37,8	22	8,3	<b>FI-SNV-12L-B-W3-DKO</b>
	15	400	11	39	40,8	27	13,3	<b>FI-SNV-15L-B-W3-DKO</b>
	18	400	13	40,5	43,3	32	18,5	<b>FI-SNV-18L-B-W3-DKO</b>
	22	250	17	45	47,8	36	26,3	<b>FI-SNV-22L-B-W3-DKO</b>
	28	250	23	46	48,8	41	44,8	<b>FI-SNV-28L-B-W3-DKO</b>
	35	250	28	53	59	50	49,8	<b>FI-SNV-35L-B-W3-DKO</b>
	42	250	35	53	60	60	75,0	<b>FI-SNV-42L-B-W3-DKO</b>
<b>S</b>	6	800	3	37	39,7	17	4,9	<b>FI-SNV-06S-B-W3-DKO</b>
	8	800	4	37	39,7	19	6,5	<b>FI-SNV-08S-B-W3-DKO</b>
	10	800	6	41	43,8	22	8,9	<b>FI-SNV-10S-B-W3-DKO</b>
	12	630	8	42	44,8	24	11,2	<b>FI-SNV-12S-B-W3-DKO</b>
	14	630	9	45	48,8	27	14,8	<b>FI-SNV-14S-B-W3-DKO</b>
	16	630	10	46	50,8	30	18,8	<b>FI-SNV-16S-B-W3-DKO</b>
	20	400	13	55	61	36	31,0	<b>FI-SNV-20S-B-W3-DKO</b>
	25	400	18	58	67	46	52,7	<b>FI-SNV-25S-B-W3-DKO</b>
	30	400	20	62	74	50	65,5	<b>FI-SNV-30S-B-W3-DKO</b>
	38	400	30	67	84	60	92,6	<b>FI-SNV-38S-B-W3-DKO</b>

Standard seal material is NBR (Buna-N®).



Please make sure to follow the assembly instructions for this product as described on page G13.