


Version A



Version B


**Adaptor  
SAD20**

Thread	Dimensions ( <sup>mm</sup> / <sub>in</sub> )		Version	Order Codes	
	G	h		NBR	FPM* (Standard Option-North America)
M16 x 1,5	39	1.54	A	SAD20/15-P-C6F	SAD20/15-V-C6F
S12* <sup>1</sup>	39	1.54	A	SAD20/12-P-C6F	SAD20/12-V-C6F
Plug in	37	1.46	B	SAD20/10-P-C6F	SAD20/10-V-C6F

**Threads**

\*1 Special thread: buttress thread S12,65 x1,5


**Metal Parts**

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**  
 For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".  
 For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".


**Sealings**

For ordering NBR sealings replace "V" with "P".  
 For ordering EPDM sealings replace "V" with "E".

\* Standard option for North America is FPM (Viton®).



Gauge Adaptor SMA20



Direct Gauge Adaptor SMD20

**Gauge Adaptor SMA20    Direct Gauge Adaptor SMD20**


Thread	Dimensions ( <sup>mm</sup> / <sub>in</sub> )			Order Codes	
	G	h	Hex A	NBR	FPM* (Standard Option-North America)
G1/4	54	19	.75	SMA20-G1/4-P-OR-C6F	SMA20-G1/4-V-OR-C6F
	2.13				
G1/2	64	27	1.06	SMA20-G1/2-P-OR-C6F	SMA20-G1/2-V-OR-C6F
	2.52				
1/4 NPT	54	19	.75	SMA20-1/4NPT-P-C6F	SMA20-1/4NPT-V-C6F
	2.13				
1/2 NPT	64	27	1.06	SMA20-1/2NPT-P-C6F	SMA20-1/2NPT-V-C6F
	2.52				
9/16-18 UNF	57	19	.75	SMA20-9/16UNF-P-C6F	SMA20-9/16UNF-V-C6F
	2.24				
G1/4	41	19	.75	SMD20-G1/4-P-OR-C6F	SMD20-G1/4-V-OR-C6F
	1.61				
G1/2	51	27	1.06	SMD20-G1/2-P-OR-C6F	SMD20-G1/2-V-OR-C6F
	2.01				
1/4 NPT	41	19	.75	SMD20-1/4NPT-P-C6F	SMD20-1/4NPT-V-C6F
	1.61				
1/2 NPT	51	27	1.06	SMD20-1/2NPT-P-C6F	SMD20-1/2NPT-V-C6F
	2.01				
7/16-20 UNF	41	19	.75	SMD20-7/16UNF-P-C6F	SMD20-7/16UNF-V-C6F
	1.61				

**Metal Parts**

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**  
 For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".  
 For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

**Sealings**

For ordering NBR sealings replace "V" with "P".  
 For ordering EPDM sealings replace "V" with "E".

\* Standard option for North America is FPM (Viton®).

Snubber on request.