Adapt[®]500 easiSpec

Seating Assessment / Specification Form

Min: 1560mm


Max: 2210mm



Min: 45 Kg


Max: 150 Kg

User Weight



User Height





Min:

1. Seat to Shoulder (Back Height)420mm640mm2. Back of Buttock to Back of Knee (Seat Depth)410mm610mm

3. Hip Width at widest point (Seat Width) 410mm 610mm
4. Floor to underside of Knee (Seat Height) 410mm 620mm*

Floor to underside of Knee (Seat Height) 410mm 6

* Higher gas columns available for use in specific environments

Max:

Adapt® 500 Seating Assessment / Specification



NB: If using a Neck support - Subtract 150mm from Nape of Neck measurement to calculate optimum back height




Please select option and state required dimensions if different




511/512 Not Available

Not Available



521/522 Not Available Not Available



531/532 Not Available Not Available Note: The Back Rest sizes on the Adapt 500 range are fixed and cannot be altered.

If you require a specific sized Back Rest (particularly if using a neck support) please refer to the Adapt 600 range which can be customised to suit virtually any requirement

Chair CODE

Width Reduction

Height Reduction


SEAT

NB: Use Back of Buttock to Back of Knee measurement and subtract 30mm to calculate the optimum seat depth

NB: Use Hip to Hip measurement and ADD + 50mm to calculate the optimum seat width



Please select option and state required dimensions if different



Chair CODE Width Reduction

Depth Reduction

440 - 500mm W: 480mm 511/521/531

REDW: to mm REDD: to mm



REDW: to mm REDD: to mm



REDW: to mm REDD: to mm



XXL (max) REDW: to mm REDD: to mm


NOTE: MINIMUM SEAT WIDTH 410mm MINIMUM SEAT DEPTH 410mm (with seat slide)

Seat Height


Please tick required option



GAS CODE Gas Lift Type



STANDARD GAS COLUMN



** NON SWIVEL GAS COLUMN



MANUAL LIFT

BASE

Please tick required option





*Standard Black Base GAS2 fitted as Standard



Polished Aluminium Base



**Pneumatic Movement Lock Non Swivel Gas fitted as Standard Please Specify Height Required (Above)

Adapt® 500 Seating Assessment / Specification

*MSA Arm is designed to support arm weight only DO NOT USE TO ASSIST WHEN SITTING OR STANDING

LEVEL ONE ADAPTATIONS





ARM PAD ENHANCEMENTS







*ADARM: Will add or subtract 50mm from arm height (measured from seat surface to top of arm pad.

Applies only to arm options marked with asterisk.

- *ADARM + 50mm
- *ADARM 50mm

*NOTE: Standard seat surface to underside of arm Arm Height is 150 - 240mm - if not suitable use ADARM option

HEAD SUPPORT

Please tick required option









HEAD REST

NECK CURVE

LEVEL TWO ADAPTATIONS


NECK ROLL


SEAT ENHANCEMENT

Please tick required option















EXTRA MEMORY FOAM SEAT



THIGH SUPPORT L/R or PAIR



/ECORE **ERGOCORE SEAT CELL**



Please specify required Seat Depth

(i.e. Back Buttock to Back of Knee L & R -30mm)

R (as sat) mm (allow for 30mm clearance behind knee) L (as sat) mm (allow for 30mm clearance behind knee)

