



FEATURES

- ▶ 0.56", 3½ digit high intensity LED display
- ▶ Available in RED, BLUE or GREEN
- ▶ User-selectable decimal points
- ▶ Polycarbonate case
- ▶ Optional bezel mount

SPECIFICATIONS

DISPLAY

Numerals Size: .56" (14.27 mm)
 Overage: three lower order digits blank for inputs >1999 & < -1999
 Polarity Indication: automatic (-) for negative
 Supply Voltage: +5 VDC @ 40 mA

INPUTS

Input Ranges: ± 200 mV, ± 2 V, ± 20 V
 Input Impedance: 1000 M Ω (200 mV)
 1 M Ω (other ranges)
 Common Mode Range: ± 1 VDC

PERFORMANCE

Accuracy: $\pm 1\%$ F.S. ± 2 counts
 Sampling Rate: 3 per second

ENVIRONMENT

Operating Temperature: 0 to 50 °C
 Max Humidity: 95% (non-condensing)

CONNECTION

12 pin

ORDERING INFO

| PART NUMBER | METER COLOR | METER INPUT |
|-------------|-------------|-------------|
| DLA-300BL | BLUE | 200mV |
| DLA-301BL | BLUE | 2V |
| DLA-302BL | BLUE | 20V |
| DLA-300GL | GREEN | 200mV |
| DLA-301GL | GREEN | 2V |
| DLA-302GL | GREEN | 20V |
| DLA-300HRL | RED | 200mV |
| DLA-301HRL | RED | 2V |
| DLA-302HRL | RED | 20V |

ACCESSORIES

| | |
|---------|---|
| DLA-BEZ | Bezel Assembly |
| PW2-5 | Regulated 120V AC to 5V DC Power Supply |
| CVC | Calibrator |



