


H-10 SLIDE GATE OPERATOR



RESIDENTIAL AND COMMERCIAL
CLASS I, II, III, & IV VEHICULAR SLIDE GATE OPERATOR

www.PerformanceGateOpeners.com | (800) 878-7829 | Sales@PerformanceGateOpeners.com



V FLEX CONTROL BOARD

- Conveniently labeled enclosure
- Ergonomically located

LCD DIAGNOSTICS DISPLAY

- Displays full error messages
- Reads real-time voltages and settings

REMOVABLE POWER SUPPLY

- Convenient fuse access
- L.E.D status indicators
- Convenient power switch
- E-Z access power outlet
- E-Z set up 115V/230V
- Included low voltage option

**NEW REDESIGNED CHASSIS
POST MOUNT READY**

MULTI-LAYER CORROSION PROTECTION

- G90 galvanized, clear zinc plating, UV rated powder coating, & 1/4" steel chassis

BUILT-IN HEATER

- Cold weather operation down to -20° F

MOTOR & BATTERY RESET SWITCHES

JBOX FOR HIGH VOLTAGE WIRING

COMPATIBLE WITH VIKING WIRELESS PRODUCTS

- Plug & Play connection for the Viking wireless expansion products.
- Viking Konnect - Wireless Kit provides secure and reliable wireless communication when the application requires two single ECUs.
- Viking Monitor - Remote access to the control board settings, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible hand held device

BATTERY BACKUP INCLUDED

- Standard Battery Backup provides 100 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operations, maximizing battery life.

LIGHTNING PROTECTION

- Advanced lightning strike protection up to 20,000 volts / 10,000 amps
- On-board surge protection monitoring.

PROTECTION

- Multi-Layer Corrosion Protection
- G90 Galvanized
- Clear Zinc Plating
- UV Rated Powder Coating
- 1/4" Steel Chassis

INTEGRATED HEATER

- Built-in heater for operating temperatures down to -20° F.
- This will allow you run your operator in the coldest conditions.

SOLAR SMART

- Power Saving technology minimizes current draw while at standby.

DIAGNOSTICS DISPLAY

- On-board LCD screen displays voltages, amps, gate status and diagnostics.

Operational Voltage	24 VDC with 1 HP Motor
Main Power Source Options	120/240 VAC Single Phase
Battery	7 AmpHr 12 VDC x 2
Battery Backup	100 Full Contin. Cycles (2200 lbs)

Operating Speed	12" Per Second
Operating Temperature	-20° F up to +160° F
Max Gate Capacity	2200 Lbs/ 75'
Max Duty Cycle	100% Contin. Cycle