

# SlideDriver™

Maximum security  
combined with extreme  
durability

The most secure slide gate operator with  
power to move any gate, customizable  
for every unique application.

## Features:



### Powerful:

Move gates up to  
20,000 lb.



### Tough:

Secure steel chassis and  
taper resistant cover.



### Reliable:

UPS models remain  
functional during a  
power outage.



### Programmable:

Configure for specific  
site requirements.



### Fast:

1-3 ft/s operating speed.  
Emergency fast operate  
at 3 ft/s.



### Smart:

Integrated primary/  
secondary controls and  
preprogrammed relay  
settings.



### All weather performance:

Wide temperature range  
without heater.



### Durable:

Decades long life and low  
maintenance.



### Made in USA:

Designed, tested and  
built within USA from  
globally sourced materials.



# SlideDriver™

Maximum security  
combined with extreme  
durability



## Technical Specifications

		FAST		FAST		
	1,500 lb gates 1 ft/s	3,000 lb gates 1.7 ft/s	4,000 lb gates 1 ft/s	5,000 lb gates 2.2 ft/s or 3 ft/s	8,000 lb gates 1 ft/s	20,000 lb gates 1 ft/s
<b>Model</b>	SlideDriver 15	SlideDriver 30F	SlideDriver 40	SlideDriver 50VF2/3	SlideDriver 80	SlideDriver 200
<b>Part #</b>	222 SS ST	222 EX 1.7 ST	222 E ST	222 X3 ST	222 X1 ST	444 XS ST
<b>Duty Cycle</b>	Continuous					
<b>Horsepower</b>	1 hp UPS model: 2 hp	2 hp	1 hp UPS model: 2 hp	2 hp	2 hp	5 hp UPS model: 4 hp
<b>Drive</b>	Hydraulic					
<b>Drive Wheels</b>	Two 6 inch (15 cm) AdvanceDrive wheels	Two 6 inch (15 cm) AdvanceDrive wheels	Two 6 inch (15 cm) AdvanceDrive wheels	Two 8 inch (20 cm) AdvanceDrive wheels	One 8 inch (20 cm) AdvanceDrive wheel, One 8 inch XtremeDrive wheel and 27 ft (8 m) of rack	Two 8 inch (20 cm) AdvanceDrive wheels, Two 8 inch XtremeDrive wheels and 52 ft (16 m) of rack
<b>Gate Weight Max.</b>	1,500 lb (680 kg)	3,000 lb (1,361 kg)	4,000 lb (1,814 kg)	5,000 lb (2,268 kg)	8,000 lb (3,629 kg)	20,000 lb (9,072 kg)
<b>Gate Length Max.</b>	Limited only by weight					
<b>Drawbar Pull</b>	300 lb (136 kg)	300 lb (136 kg)	300 lb (136 kg)	300 lb (136 kg)	600 lb (272 kg)	1,200 lb (544 kg)
<b>Rate of Travel</b>	1 ft/s (30 cm/s)	1.7 ft/s (50 cm/s)	1 ft/s (30 cm/s)	Field adjustable, 2.2 ft/s (70 cm/s) or 3 ft/s (91 cm/s) Emergency Fast Operate 3 ft/s (91 cm/s)	1 ft/s (30 cm/s)	1 ft/s (30 cm/s)
<b>Temperature Rating</b>	-40° to 158° F (-40° to 70° C)					
<b>1 Phase Power</b>	115/208/230V 60 Hz 110/220V 50 Hz***	208/230V 60 Hz 220V 50 Hz***	115/208/230V 60 Hz 110/220V 50 Hz***	208/230V 50/60 Hz	208/230V 60 Hz 220V 50 Hz***	230V 60 Hz 220V 50 Hz***
<b>3 Phase Power</b>	208/230/460V 60Hz; 220/380/440V 50Hz***			208/230V 50/60Hz or 380/460V 50/60Hz	208/230/460V; 220/380/440V 50Hz***	
<b>Included Accessories</b>	One premium EMX IRB-MON photo eye, one 5-foot premium ASO edge sensor and a pre-wired Hy2NC adapter					Pre-wired Hy2NC adapter
<b>Communication</b>	RS-232, RS-485					
<b>User Controls</b>	Smart Touch Controller with 70+ configurable settings, programmed via the keypad and display or a PC using S.T.A.R.T. software.					
<b>Relay</b>	Three configurable user relays: one 30VDC, 3A solid state and two 250VAC, 10A electromechanical; Optional Hy8Relay™ for 8 additional relay outputs					
<b>Finish</b>	Zinc plated with powder coating					
<b>ETL Listed (UL 325)</b>	Usage Class I, II, III, IV	Usage Class III, IV	Usage Class I, II, III, IV	Usage Class III, IV	Usage Class III, IV	Usage Class III, IV
<b>Warranty</b>	5 year w/product registration					
<b>UPS Battery Backup Power and Additional Models</b>						
<b>DC Power Supply* † with HyCharger DC</b>	SlideDriver 15 UPS	SlideDriver 30F UPS	SlideDriver 40 UPS	–	SlideDriver 80 UPS	SlideDriver 200 UPS**
<b>AC Power Supply with HyInverter AC*</b>	SlideDriver 15 with HyInverter AC	–	SlideDriver 40 with HyInverter AC	SlideDriver 50VF2/3 with HyInverter AC	–	–
<b>Correctional Facility</b>	–	SlideDriver 30F-C	SlideDriver 40-C	SlideDriver 50VF2/3-C	SlideDriver 80-C	SlideDriver 200-C
<b>Modular</b>	SlideDriver 15-M	SlideDriver 30F-M	SlideDriver 40-M	SlideDriver 50VF2/3-M	SlideDriver 80-M	–


\*3,000 ft/hr expected duty cycle. The operator's normal duty cycle and the actual number of gate cycles available from battery depends upon gate resistance to travel, cycle length, battery size, state of charge and health, ambient temperature, accessory power draw and frequency of gate cycles during power outage.  
 \*\* SlideDriver 200 UPS has a 2,000 ft/hr (610 m/hr) expected duty cycle. Actual duty cycle depends on site specific conditions and gate configuration.  
 \*\*\*Refer to Installed Options on pricing for all 50Hz voltages, which are special order.  
 † 115V DC Power Supply requires a 30A branch circuit. Choose voltage with care as chargers are not field convertible.



support.hysecurity.com

Nice/HySecurity is an industry leader of automated gate and perimeter security solutions.

The HySecurity brand provides high-quality, ultra-reliable industrial gate operators and crash-rated, Hostile Vehicle Mitigation (HVM) vehicle barriers designed to secure and protect critical infrastructure and facilities worldwide.



©2023 Nice North America LLC. HySecurity is a registered trademark of Nice North America LLC. All rights reserved.  
 All trademarks, logos and brand names are the property of their respective owners.