Models # MLC-K36, MLC-K72

Monitored Light Curtain

Applications

• Sectional Doors

Coiling
Doors

An invisible curtain of protection

Using a series of thru beam photo eyes attached near the door track or guides, this light curtain is designed to provide a dense barrier of light that, when interrupted, signals the door to reverse. With the ability to span up to 32 feet wide and 6 feet high, it is suitable for use on the majority of commercial and industrial door applications.

The Miller Edge Light Curtain is a UL-325 compliant monitored device that replaces a photo eye and provides extended protection.

* Non-Monitored models are available, please contact factory.

FUNCTIONAL BENEFITS:

- UL-325 approved
- Waterproof housing (IP67)
- No external interface box required
- Simplified wiring
- Includes mounting brackets for easy installation

SPECIFICATION:

OPTICAL:

Max. Operating Range: 32 feet No. of Elements: 8 or 16 Max. Ambient Light: >100,000 Lux Aperture Angle: Tx: ± 10° and Rx: ± 20°

ELECTRICAL:

Status LED Rx: Object Detected: RED Power OK: GREEN Power LED Tx: Power OK : GREEN Supply Voltage: 12...24 VAC/DC Current Consumption: < 100 mA @ 24 VDC

MECHANICAL:

Cross Section: 1.0 in x 1.1in Max. Physical Height: 38 in and 74 in Max. Protection Height: 36 in and 72 in Housing Material: Black PVC over aluminum Enclosure Rating: IP67 Temperature Range: - 40° C... + 60° C (- 40° F... + 140° F)




MLC-K36

Light Curtain Kit: 3 foot coverage Includes: MLC-E36 Emitter + MLC-R36 Receiver with 3' cable attached + mounting brackets

MLC-K72

Light Curtain Kit: 6 foot coverage Includes: MLC-E72 Emitter + MLC-R72 Receiver with 3' cable attached + mounting brackets

ELECTRICAL CONNECTION:



MLC-K36/MLC-K72_Spec_20150804



P.O. Box 159 • West Grove, PA 19390 • (610)869-4422 • Fax: (610)869-4423 • 800-220-3343 6809 South Harl Avenue, Suite A, Tempe, AZ 85283 • (480)755-3565 • Fax (480)755-3558 • 800-887-3343 www.milleredge.com

FC c SU us