# Slide Gate Operator 7251/7351







### 12VDC battery powered\*

## Operator for sliding gates up to 800 lbs and 25 ft

Recommended for high cycle residential and light commercial applications

Solar compatible

Nice OXI/A Receiver and ABF/A Antenna Kit included







#### \*Battery required but is not included

**Versatile:** Available in 7251 post mount and 7351 pad mount. Supplied with 35 ft #40 roller chain.

**Solar compatible:** 12V battery (required) can be charged by either solar or AC power.

**Easily installed** on most existing or new slide gates. The operator has internal limit switches and quick release system.

## Both models use the advanced 1050 control board offering:

- LCD display for easy programming, diagnosing and troubleshooting
- Includes OXI/A receiver and ABF/A antenna kit
- Supports up to 1000 Inti or Era One remotes with rolling-code security
- Smart battery charging management
- Integrated 7 day programmable timer
- Surge protection
- Nice BlueBUS 2-wire technology self-identifies monitored photo eyes

**Quality and durability**: Rugged enclosure with weather resistant NEMA 3R, powder coated black. Structural components are treated with a durable coating to minimize corrosion.

Single or dual gate applications

Model	Description	Approvals
7251	Operator, 12VDC, post mountable, for sliding gates up to 25 ft and 800 lb, includes 1050US, UL325 6th Edition Compliant	ETL
7351	Operator, 12VDC, pad mountable, for sliding gates up to 25 ft and 800 lb, includes 1050US, UL325 6th Edition Compliant	ETL
Technical Spe	ecifications	
Model	7251 / 7351	
Electrical dat	a	
Voltage Inpu	ut 12 - 30VDC	
Operating V	oltage 12VDC	
Idle Current	10mA	
Performance	data	
Rate of Trav	rel 1 ft/s	
Duty Cycle (	(cycles/hour) Varies based on charging capacity	
Dimensions a	and general data	
Temperature	e Rating -40° to 150° F (-40° to 65° C)	
Dimensions	7251: 22w x 22h x 15.5d / 7351: 26.5w x 20.5h x 18d inches	