



## TOP SECRET COATINGS

1999 Elizabeth St North Brunswick, NJ 08902  
Phone: 732-821-3200 Fax: 732-821-8180  
info@topsecretcoatings.com  
www.topsecretctings.com

---

### TS-107 Court-Coat

### A Slam-Dunk

**Court-Coat** is a new generation single stage epoxy-ester that is oxygen cured making it the latest in activity and court coatings technology. It is a next generation epoxy that eliminates the need for mixing multiple components together and the hassle and complications of limited pot life. The low odor formula produces a nontoxic film making it friendly to you and the environment. We think this combination of features makes it a compelling choice.

For the first time anyone that can roll up their sleeves and run a paint roller can create a highly durable court acceptable for professional sports venues. It easily creates a high build finish that saves you time, labor and money. Adhesion, film build, hide, coverage, hardness, scuff and impact resistance are all excellent. It resists the damaging effects of UV, harsh chemicals and staining agents. It is a fully waterproof barrier coating that stops the movement of both water and vapors.

Sport-Court is available in 100 colors and is self priming in most applications. It adheres to a wide variety of surfaces including concrete, wood, asphalt and masonry. Designed as a self priming system in two or three coats. To control ball speed add aggregate Court-Coat #1, #2 or # 3 aggregate additive. Practical coverage is 250-275 square feet per gallon depending on porosity. Available in one gallon or five gallon containers.

#### Product Features:

- Eliminates the need for mixing multiple components.
- A fully submersible barrier to water and gasses.
- Acceptable for interior and exterior applications.
- Produces a hard scuff resistant surface.
- Acceptable for interior and exterior applications.
- Superior color retention.
- Easy to apply
- Resists cracking and peeling.

# PERFORMANCE DATA SHEET

## TS-107 Court-Coat

**COLOR(S):** 100 + colors and clear

**PRODUCT TYPE:** Acrylic latex

**DESCRIPTION:** TS-107 is a no-mix acrylic latex fortified with epoxy to improve long term durability and performance. It is acceptable for use on all exterior or interior sports court surfaces including wood and concrete surfaces.

### PHYSICAL CHARACTERISTICS

**VISCOSITY:** N/A

**DRY TO TOUCH:** 1-2 hours

**WEIGHT SOLIDS:** 50%

**VOLUME SOLIDS:** N/A

**RECOAT:** 12-24 hours

**WEIGHT PER GALLON:** N/A

**V.O.C. :** < 100 g/L

**FLASH POINT:** 100° F.

**PACKAGING:** 1 or 5 gallons

**BATCH:** To Order

**PRACTICAL COVERAGE:** 250-300 square feet per gallon

**SURFACE PREPARATION:** Surface to be coated must be free of all loose dirt or scaling paint and any other foreign material. All loose material should be removed before painting. We recommend cleaning with TS-695 Etching cleaner. Allow to dry before applying coating.

**APPLICATION:** Best when applied by roller coat in two or more coats. Recommend waiting 12-24 hours in between coats.

**THINNING:** Thin if necessary with water.

**CLEAN-UP:** Tools and equipment may be cleaned with soap and water