



Decade DECK PAINT

PO. Box 3007, Arlington WA. 98223
360-651-9050 FAX 360-548-8573

TS-190 Decade Deck Paint

The Best Deck Paint Available Today!

Decade Deck Paint promises to last longer than home center or hardware store brands! It offers superior adhesion, without cracking or peeling, which has got to be good news for those fed-up with repainting their deck every year. Decade *really lasts* — it may be the best deck paint available on the market today making it an excellent value.

Users love the easy application, long lasting durability and beauty it provides. The low odor low VOC formula is friendly to you and the environment. Decade uses advanced resin technology proven to withstand decades of intense UV, wind, rain and climatic extremes. It produces a remarkably durable finish that remains both hard and flexible at the same time. Even after decades it remains flexible enough to expand and contract with wood without peeling.

Decade provides long lasting protection to dimensional decking surfaces subject to extremes in weather (-20 +140F). Decade is acceptable for use on a wide variety of surfaces including cedar, pine, fir, synthetic (Trex), pressure treated wood and composite materials. It may be applied directly to any of these surfaces without primer, in two or more coats. No specialized training is required to apply it. Anyone that can operate a paint roller can do it themselves in one day. An environmentally friendly low odor formula that produces a nontoxic finish. Finish is satin.

PRODUCT FEATURES

- Lasts longer making it an excellent value.
- Self-priming in two or more coats.
- Remains flexible for a decade!
- Provides unequalled UV resistance.
- High adhesion combined with good hardness.
- One gallon covers 150-200 square feet.
- Low VOC, low odor.
- Acceptable for use on pressure treated wood.
- Available in 100 colors.

TS-190

PERFORMANCE DATA

TS-190 Decade 20-Year Deck Paint

COLOR(S): Wide range of colors and tint bases.

PRODUCT TYPE: Pigmented, waterborne acrylic latex polymer.

DESCRIPTION: A premium quality elastomeric acrylic solid stain suitable for most all exterior structural surfaces. Suitable for bare wooden surfaces, designed for use on properly prepared wooden surfaces including decks, railings, stairs, docks or ramps. Blocks most tannin stains with first coat. Not intended for submersion duty.

PHYSICAL CHARACTERISTICS:

DRY TO TOUCH: 1hour

DRY HARD: 24 hours

WEIGHT SOLIDS: 50%

VOLUME SOLIDS: 35%

TACK FREE: 30 minutes

TIME TO RECOAT: 24 hours, weather dependent

VISCOSITY: 90-100 K.u.

WEIGHT PER GALLON: 10.8 lbs. per gal.

V.O.C.: < 100 grams per liter

FLASH POINT: N/A.

PACKAGING: 1 or 5 gallon containers

PRACTICAL COVERAGE: 150-200 square feet per gallon @ 10 mils wet film thickness.

SURFACE PREPARATION: Clean all surfaces of corrosion, oil, grease, grime, and any existing paint lacking good adhesion. For glossy surfaces, prepare the surface by sanding lightly or applying liquid sandpaper to dull finish prior to application. **Bare Wood, Composite Siding Including Painted Surfaces:** Must be dry, thoroughly clean and free of dirt, grime, oil, grease, wax, mold, mildew and contaminates. Sanding is recommended on all surfaces for best results.

APPLICATION: May be brushed, rolled or sprayed. Apply a minimum of two coats to achieve a minimum Dry Film Thickness (DFT) of 15 mils. Roller-Coat: Recommend using a 5/8"-3/4" non-shedding roller cover. Spray: Apply a minimum of two coats to achieve minimum DFT. Brush: Apply a minimum of two coats evenly to achieve recommended DFT. Do not allow to get rain wet for 48 hours after application. Do not apply when rain is in the forecast within 48 hours. Do not apply below 50F or above 85F. Avoid applying in hot direct sunlight.

THINN & CLEAN UP: Thinning not usually required. Thin if necessary with clean water. Clean tools and equipment immediately with soap and water.