



TOP SECRET COATINGS

1999 Elizabeth St No. Brunswick, NJ 08902

P: 732-821-3200 Fax: 732-821-8180

info@topsecretcoatings.com

www.topsecretcoatings.com

TS-4 Urethane Reinforced Alkyd

Colors & Clears Available

Now One Enamel Does it All!

TS-4 Urethane Reinforced Alkyd is an advanced blend of resins that can be used almost anywhere and in most any application. This exceptionally durable enamel is so adaptable, so durable you will want to use it in a wide variety of industrial, marine, commercial and consumer applications.

Brush it on and watch the marks disappear before your eyes! It self levels like a dream. Now for the first time you can brush or roll your job and it will look sprayed! It creates a high-gloss self leveling waterproof film that remains both hard and flexible at the same time!

It adheres to almost anything, inhibits rust, resistant to chemicals, spilled fuel and many dilute acids. It has high impact resistance, heat resistance, it's color-fast, UV resistant, non-chalking and it resists cracking, chipping and peeling. It offers outstanding performance in Marine, Industrial, Floor, Roof, Automotive, Commercial, Farm and at Home applications.

It offers outstanding adhesion to Metal, Wood, Concrete, Masonry, Ceramic Tile, Asphalt, Vinyl, Plastic, Fiberglass and Composite surfaces. Economical to use and covers in just one coat. Our lead-free formula is low VOC, non-toxic, and child safe.

PRODUCT FEATURES

- Outstanding Resistance To Chemicals, Fuel & Salt
- Superior Adhesion, One Coat Coverage
- Excellent Hardness, Durability, Highly Flexible
- Easy To Clean, No More Waxing Or Buffing
- Non-yellowing, UV Stable, Colorfast
- Waterproofs, Seals, Protects, Inhibits Rust
- Superior Gloss Retention
- Excellent Abrasion & Mar Resistance
- Easy Application, Low Maintenance
- High Solid, Low VOC, Low Odor Formula
- Self Leveling Formula
- Resists Chipping, Cracking & Peeling
- Economical To Use, No Clear Coat Required
- Self Priming In Many Applications
- Acceptable for Indoor/Outdoor Use
- Wide Variety Of Application Possibilities

PERFORMANCE DATA

TS-4 Urethane Reinforced Alkyd (Single Component)

COLOR(S): Available in 100+ colors and clear

PRODUCT TYPE: Urethane reinforced alkyd

DESCRIPTION: A premium quality single component urethane reinforced alkyd for use in commercial, industrial, manufacturing, and marine applications. It offers tremendous durability and ease of application. Available in satin and gloss.

PHYSICAL CHARACTERISTICS:

VISCOSITY: N/A

WEIGHT SOLIDS: 60%

VOLUME SOLIDS: N/A

TACK FREE: 5 hours

TIME TO RECOAT: 6 hours

POT LIFE: N/A Product is a one part

WEIGHT PER GALLON: 10.75 lbs. per gal.

DRY HARD: 8 hours

DRY TO TOUCH: 4 hours

TEMPERATURE TO BE APPLIED: 50-90 Degrees Fahrenheit

V.O.C : < 450 g/L

FLASH POINT: N/A

PACKAGING: single gallons or 5 gallon containers

APPLICATION: Can be brushed, rolled, or sprayed onto surfaces

THINNING: Thin with TS-101 Thinner or Mineral Spirits

CLEAN-UP: Tools and equipment may be cleaned immediately with TS-101 or TS-605 Thinners, acetone or lacquer.