

TOP SECRET COATINGS

P.O. Box 3007, Arlington WA. 98223
 Phone: 360-651-9050 Fax: 360-548-8573
 info@topsecretcoatings.com
 www.topsecretcoatings.com



TS-631 Shell-Tex Non-Slip Additive for Paint

Wears At The Same Rate As Paint

Shell-Tex TS-631 is an additive for paint and coating products that creates a textured slip resistant finish to any surface. It is acceptable for use with virtually any floor coating product including epoxy, urethane, acrylic and alkyd and 100% solids products.

Unique because it utilizes finely ground walnut shells to produce the textured finish. It is well liked in this application because it wears at the same rate as typical paint and coating products extending the life of the finish. It suspends well and produces an even finish.

Use Shell-Tex to improve slip resistance or simply to add decorative texture to a finish. It is acceptable for use with both oil and water based products. It is acceptable for brush and roller-coat applications and it is sprayable with a large size tip. Not a hazardous material. Safe and easy to use. Color is tan.

SURFACES: Decks, floors, steps, patios, walkways, laundry rooms, kitchens, basements, pool decks, handrails, bathrooms. Acceptable for use on wood, concrete, masonry, metal, fiberglass, plastic and drywall.

DIRECTIONS: Pour contents of package into liquid coating product, mix thoroughly, apply evenly. No induction time is required. Recommend using 8 dry ounces per gallon.

FEATURES:

- Adds a slip resistant texture to paint and coating products.
- Stays suspended better than heavier additives.
- Wears at a similar rate as most coating products.
- Adds a decorative appearance where desired.
- Acceptable for brush, roll or spray applications.