

1. Identification

Product Identifier: **EasyFlo 60 Liquid Plastic Part A**
EasyFlo 95 Liquid Plastic Part A
EasyFlo 120 Liquid Plastic Part A
EasyFlo 100 FR Liquid Plastic Part A
EasyFlo Clear Liquid Plastic Part A
EasyFlo Spray FR Liquid Plastic Part A

Product Code(s): EZFLO60A, EZFLO95A, EZFLO120A, EZFLO100FRA, EZCLRA, EZSPRAYFRA

Use: Component for Polyurethane Casting/Mold Shell Plastic. For Industrial/Professional use only.

Manufacturer: Polytek Development Corp.
 55 Hilton St., Easton, PA 18042

Phone Number: 610-559-8620 (9 a.m. to 5 p.m. EST)

Emergency Phone: CHEMTREC 800-424-9300 or +1 (703) 527-3887

E-mail: sds@polytek.com

2. Hazards Identification

GHS Classification:

Acute Inhalation Toxicity Category 4
 Skin Irritation Category 2
 Eye Irritation Category 2
 Respiratory Sensitization Category 1
 Skin Sensitization Category 1
 Carcinogenicity Category 2
 Specific Target Organ Toxicity Single Exposure Category 3 (respiratory irritation)
 Specific Target Organ Toxicity Repeated Exposure Category 2

Label Elements: Danger



Hazard Phrases

H332 Harmful if inhaled.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H373 May cause damage to lungs and respiratory system through prolonged or repeated exposure.

Precautionary Phrases

P202 Do not handle until all safety precautions have been read and understood.
 P261 Avoid breathing mist, vapors or spray.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves, protective clothing, eye protection, and face protection.
 P312 Call POISON CENTER/doctor if you feel unwell.
 P302+352 IF ON SKIN: Wash with plenty of soap and water.
 P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+313 If skin irritation occurs: Get medical advice/attention.
 P337+313 If eye irritation persists: Get medical advice/attention.
 P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

P362+364 Take off contaminated clothing and wash before reuse.
 P403+233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents and container in accordance with local, regional and national regulations.

Supplemental Information: Individuals sensitized to isocyanates should discontinue use. Long-term overexposure to isocyanates may cause lung damage.

This is one part of a two-part system. Read and understand the hazard information on part B before using.

3. Composition/Information on Ingredients

Chemical Name	CAS #	%
Methylenediphenyl Diisocyanate (MDI)	26447-40-5	50-70%

4. First-Aid Measures

Eye Contact: Rinse thoroughly with water for at least 15 minutes, holding the eyelids open to be sure the material is washed out. Get prompt medical attention.

Skin Contact: Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use. Discard items that cannot be decontaminated.

Inhalation: Remove person to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Get medical attention.

Most Important Symptoms/Effects: Causes skin and eye irritation. Vapors or mists may cause respiratory irritation. May cause allergic skin and/or respiratory reaction in sensitized persons. Symptoms include skin rash, wheezing, shortness of breath and other asthma symptoms. Prolonged inhalation overexposure may damage the lungs and respiratory system.

Indication of Immediate Medical Attention/Special Treatment:

Immediate medical attention is required for asthmatic symptoms or serious inhalation exposures. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Persons sensitized to Diisocyanates should consult a physician regarding working with respiratory irritants or sensitizers.

5. Fire-Fighting Measures

Extinguishing Media: Use water fog, foam, carbon dioxide or dry chemical. Do not use solid water stream. Solid stream of water into hot product may cause violent steam generation or eruption.

Specific Hazards: Not classified as flammable or combustible. Product will burn under fire conditions.

Special Protective Equipment & Precautions for Fire-Fighters: Wear positive pressure, self-contained breathing apparatus and full-body protective clothing. Cool fire-exposed containers with water.

6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency

Procedures: Remove all ignition sources. Clear non-emergency personnel from the area. Wear appropriate protective clothing to prevent eye and skin contact and avoid breathing vapors. Ventilate area. Caution – spill area may be slippery.

Methods and Materials for Containment and Cleanup: Cover with an inert absorbent material and collect into an appropriate container for disposal. Do not seal the container since CO₂ is generated on contact with moisture and dangerous pressure buildup can occur. Decontaminate floor area with a mixture of water plus isopropyl alcohol (20%),

household ammonia (10%), and detergent (2%).

7. Handling and Storage

Safe Handling: Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep container closed when not in use.

Safe Storage: Store indoors at temperatures between 60°F and 95°F. Store in original, unopened containers. Protect from atmospheric moisture and water since MDI reacts with water to form CO₂ leading to potentially dangerous pressure build up in sealed containers.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits:

Chemical Name	Exposure Limits
Methylenediphenyl Diisocyanate (MDI)	0.02 ppm (C) OSHA PEL 0.005 ppm TWA ACGIH TLV

Ventilation: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

Respiratory Protection: If needed, an approved respirator with organic vapor cartridges may be used. Respirator selection and use should be based on contaminant type, form and concentration. For higher exposures or in an emergency, use a supplied-air respirator.

Skin Protection: Wear impervious gloves, such as butyl rubber or nitrile rubber.

Eye Protection: Wear chemical safety goggles.

Other Protective Measures: Wear impervious clothing to prevent skin contact and contamination of personal clothing. An eye wash facility and washing facility should be available in the work area. Follow applicable regulations and good Industrial Hygiene practice.

9. Physical and Chemical Properties

Appearance: Clear, yellow liquid

Odor: Mild, acrid

Odor Threshold: 0.4 ppm (MDI)

pH: Not applicable

Melting Point: No data available

Boiling Point: No data available

Flash Point: >149°C (300°F)

Evap. Rate: No data available

Flamm. Limits: No data available

Vapor Pressure: ≤0.0007 mm Hg @ 20°C (MDI)

Vapor Density: No data available

Relative Density: 1.1 @ 25°C

Solubility: Insoluble in water

Partition Coefficient: n-octanol/Water: Reacts with water

Auto-Ignition Temp: No data available

Decomposition Temp: No data available

Viscosity: ≤150 cP

10. Stability and Reactivity

Reactivity: Diisocyanates react with many materials and the rate of reaction increases with temperature. Reaction with water generates carbon dioxide and heat.

Chemical Stability: Stable under recommended conditions.

Possibility of Hazardous Reactions: Elevated temperatures can cause hazardous polymerization. Polymerization can be catalyzed by strong bases or water. Reaction with water generates carbon dioxide, and results in heat and pressure buildup in closed systems.

Conditions to Avoid: Avoid moisture and temperatures below 60°F and above 95°F to protect product integrity.

Incompatible Materials: Avoid contact with water, acids, bases, alcohols, strong oxidizers, and some metals (e.g., aluminum, zinc, brass, tin copper).

Hazardous Decomposition Products: Possibly isocyanate vapor, carbon monoxide, nitrogen oxides, and traces of hydrogen cyanide. Gases are released during decomposition.

11. Toxicological Information

Eye Contact: May cause moderate irritation. May cause temporary corneal injury.

Skin Contact: May cause irritation. May stain skin. Repeated skin contact may cause an allergic skin reaction. Animal studies indicate that skin contact with isocyanates may affect potential respiratory sensitization.

Inhalation: At room temperature, vapors are minimal due to low volatility. Vapors or aerosols (e.g., generated during heating or spraying) may cause respiratory irritation and possibly pulmonary edema. May cause respiratory sensitization. For individuals sensitized to MDI, exposure may result in allergic respiratory reactions (e.g., coughing, wheezing, difficulty breathing).

Ingestion: Single oral dose toxicity is low. No harmful effects anticipated from ingesting small amounts incidental to normal handling. Large amounts may cause gastrointestinal effects.

Chronic Health Effects: Repeated or prolonged exposure to isocyanates above exposure limits may cause an allergic sensitization of the respiratory tract causing an asthma-like response upon re-exposure. Repeated overexposure to isocyanates has been associated with decreased lung function. Repeated or prolonged dermal contact with this product may cause allergic skin sensitization in some individuals.

Acute Toxicity Values:

MDI: Oral rat LD50 >10,000 mg/kg; Skin rabbit LD50 >9,400 mg/kg;

Inhalation rat LC50 0.49 mg/L/4 hr (aerosol)

Skin Corrosion/Irritation: Irritating to the skin.

Eye Damage/Irritation: Irritating to the eyes.

Respiratory Irritation: Vapors and mists are irritating to respiratory system.

Respiratory Sensitization: Isocyanates are respiratory sensitizers.

Skin Sensitization: Isocyanates are skin sensitizers.

Germ Cell Mutagenicity: Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.

Carcinogenicity: Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI. MDI is not designated as a carcinogen by NTP, IARC, or OSHA.

Reproductive Toxicity: In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother.

Specific Target Organ Toxicity:

Single Exposure: No data available

Repeat Exposure: Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

12. Ecological Information

Ecotoxicity:

Diisocyanates: The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Persistence and Degradability:

Diisocyanates are not readily biodegradable.

Bioaccumulative Potential: Diisocyanates are not expected to bioaccumulate.

Mobility in Soil: In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

13. Disposal Considerations

Dispose according to local, state and federal regulations. Upon exposure to moisture, product forms an inert, non-hazardous solid.

For U.S.: Upon disposal, this product is not a RCRA hazardous waste (per 40 CFR 261).

14. Transport Information

Not regulated for transport in any mode.

EMERGENCY SHIPPING: CHEMTREC, 800-424-9300 or +1-703-527-3887

15. Regulatory Information**U.S. FEDERAL REGULATIONS:**

CERCLA 103 Reportable Quantity: This product is not subject to reporting under CERCLA. Some states have more stringent reporting requirements. Report all spills in accordance with local, state, and federal regulations.

SARA TITLE III

Section 311/312: Acute Health, Chronic Health

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements:

Diisocyanates Category	50-70%
------------------------	--------

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on TSCA.

STATE REGULATIONS:**California Proposition 65:**

EasyFlo 100 FR Liquid Plastic Part A: WARNING: This product can expose you to chemicals including Di-isodecyl phthalate (DIDP), which is known to the State of California to cause reproductive harm.
www.P65Warnings.ca.gov

EasyFlo 120 Liquid Plastic Part A: WARNING: This product can expose you to chemicals including Butyl benzyl phthalate (BBP), which is known to the State of California to cause reproductive harm.
www.P65Warnings.ca.gov

EasyFlo 60 Liquid Plastic Part A, EasyFlo 95 Liquid Plastic Part A, EasyFlo Clear Liquid Plastic Part A, EasyFlo Spray FR Liquid Plastic Part A: These products do not contain substances known to the State of California to cause cancer and/or reproductive harm.

16. Other Information

Training Advice: All personnel using/handling this product should be trained in proper chemical handling and the need for and use of engineering controls and protective equipment.

Recommended Uses and Restrictions: This product is intended for industrial or professional use only.

SDS Revision Notes: Updated Prop 65 Warning, August 30, 2018; 3/20/18 Removed EZFlo 9011/7/17 Added EasyFlo 90A. Added EasyFlo120A and EasyFlo Clear A to this SDS. Modified CA Prop 65 information in Section 15 and made other minor corrections.

Disclaimer: The information contained herein is considered accurate; however, Polytek makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.