



# LCD Throttle P-Settings (QS-S4)

**For Models:**  
City / City plus  
Tour 1.0  
Pro / Pro plus / Pro-R

**EVOLV**

PAGE NO.	PAGE DESCRIPTION	EVOLV CITY / CITY PLUS	EVOLV TOUR (First Gen.)	EVOLV PRO / PRO-R
P01	Backlight brightness Range: 1-3 Dim: 1 Bright:3 Default:3	3	3	3
P02	Mileage unit of measure Default: KM-000 Mi-001	Dependent upon final country of origin.	Dependent upon final country of origin.	Dependent upon final country of origin.
P03	Battery voltage specification 24V, 36V, 48V, 52V, 60V	36V / 48V	48V	52V / 60V
P04	Display timeout in minutes Range: 0 - 60 Default: 5 Display will not timeout: 0	5	5	5
P05	Reserved page	0	0	0
P06	Wheel diameter Accuracy is 0.1 Default: 10.0	8 Inches	8.5 Inches	10 Inches
P07	Magnet count for measuring speed Default: 28 Range: 0 - 255	28	28	28
P08	Available power for use Range: 0 - 100%	100	100	100
P09	Kick to engage motor ON:001 OFF:000 (Safety / ease of use)	ON: 001	ON: 001	ON: 001
P10	Reserved page	0	0	0
P11	Electronic braking Range: 1 - 5 Weak: 1 Strong: 5	1	1	1
P12	Acceleration strength Range: 1 - 5 Soft: 1 Strong: 5	3	3	3
P13	Reserved page	0	0	0
P14	Reserved page	0	0	0
P15	Low voltage cut-off Default: 42V	30.5V / 39.6V	39.6V	42.6V / 49V
P16	Odometer readout and clearing (for some versions). Press and hold $\pm$ for 5 seconds to reset readout.	ODO	ODO	ODO
P17	Cruise control ON:1 OFF:0	OFF: 0	OFF: 0	OFF: 0
P18	Reserved page	0	0	0
P19	Reserved page	0	0	0
P20	Communication protocol Default: 4 Cannot be changed	4	4	4