

GermAwayUV Sanitation Conveyor System



EPA Est No. 94850-FL-1

The ideal solution for disinfecting high quantities of small items rapidly

TECHNICAL SPECIFICATIONS


INFO **CONVEYOR SPEED:** 0-16 FEET PER MINUTE GERMICIDAL OVEN ENTRY/EXIT HEIGHT: ADJUSTABLE UP TO 6" UV BULB RATED LIFE: 10,000 HOURS **UV-C POWER:** 320WATTS CONVEYOR WIDTH: 16" **VOLTAGE:** 120V (220V UNITS AVAILABLE AS WELL) UV BULBS USED: UV GERMICIDAL AREA: 40" X 16"

KEY FEATURES

- · 253.7nm UV light clinically proven to eliminate pathogens, germs and viruses.
- · Variable belt speed
- Run multiple types of items through conveyor with ease.
- Long bulb life and easy bulb replacement.

DOSAGE AT VARYING CONVEYOR SPEEDS

Speed	Dosage from Above	Dosage from Below
1	557 mJ/cm2	247 mJ/cm2
2	403 mJ/cm2	196 mJ/cm2
3	312 mJ/cm2	173 mJ/cm2
4	269 mJ/cm2	116 mJ/cm2
5	243 mJ/cm2	127 mJ/cm2
6	204 mJ/cm2	101 mJ/cm2
7	185 mJ/cm2	100 mJ/cm2
8	167 mJ/cm2	78 mJ/cm2
9	155 mJ/cm2	65 mJ/cm2
10	140 mJ/cm2	57 mJ/cm2







ADDITIONAL INFORMATION

For more information of any of our products or services please visit us on the Web at:

www.cureuv.com

This document is copyright @ August 13, 2020 CureUV. All rights reserved. This document is provided for information purposes only. Contents are subject to change without notice. It is not warranties to be error-free. Nor subject to any other warranties or conditions including implied warranties and conditions of merchantability or fitness for a particular purpose.



Phone: (800) 977-7292

Address: 2855 S. Congress Ave. Ste. C, Delray Beach, FL, 33445

Web store: www.cureUV.com