



Revision Number: 005.0

Issue date: 01/05/2009

1. PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|-------------------------|--|-----------------------------|--|
| Product name: | LOCTITE® 3922™ LIGHT CURE ADHESIVE PART NO. 32047 | IDH number: | 312054 |
| Product type: | Ultraviolet adhesive | Item number: | 32047 |
| Company address: | Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067 | Region: | United States |
| | | Contact information: | Telephone: 860.571.5100 Emergency telephone: 860.571.5100 Internet: www.henkelna.com |

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

| | | | |
|------------------------|-------------|-----------------------------|--------------------|
| Physical state: | Liquid | HEALTH: | *2 |
| Color: | Pale yellow | FLAMMABILITY: | 2 |
| Odor: | Mild | PHYSICAL HAZARD: | 1 |
| | | Personal Protection: | See MSDS Section 8 |

WARNING: COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL IF SWALLOWED, ABSORBED THROUGH SKIN OR INHALED.
DO NOT SPRAY. DO NOT HEAT.
MAY CAUSE ALLERGIC SKIN REACTION.
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

| | |
|----------------------|---|
| Inhalation: | Modified acrylamide is harmful if inhaled. Vapors and mists will irritate nose and throat and possibly eyes. Causes respiratory tract irritation. Nausea. Headache. DO NOT heat or spray as this increases the inhalation hazard. |
| Skin contact: | Modified acrylamide may be absorbed through skin in harmful amounts. Toxic. May cause allergic skin reaction. Causes skin irritation. |
| Eye contact: | Contact with eyes will cause irritation. |
| Ingestion: | Modified acrylamide is harmful if swallowed. Toxic. |

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous components | CAS NUMBER | % |
|----------------------|-------------|---------|
| Acrylate monomer | Proprietary | 30 - 60 |
| Urethane Polymer | Proprietary | 30 - 60 |
| Modified acrylamide | 2680-03-7 | 10 - 30 |
| Substituted silane | Proprietary | 1 - 5 |
| Photoinitiator | Proprietary | 1 - 5 |

4. FIRST AID MEASURES

| | |
|----------------------|--|
| Inhalation: | Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention. |
| Skin contact: | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. If symptoms develop and persist, get medical attention. |
| Eye contact: | Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get immediate medical attention. |
| Ingestion: | Do not induce vomiting. Keep individual calm. Never give anything by mouth to an unconscious person. Get immediate medical attention. |

5. FIRE FIGHTING MEASURES

| | |
|--|--|
| Flash point: | 73.9 °C (165.02 °F) Pinsky Martens closed cup |
| Autoignition temperature: | Not available |
| Flammable/Explosive limits - lower: | Not available |
| Flammable/Explosive limits - upper: | Not available |
| Extinguishing media: | Foam, dry chemical or carbon dioxide. |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. |
| Unusual fire or explosion hazards: | Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers. |
| Hazardous combustion products: | Oxides of carbon. Oxides of nitrogen. Oxides of phosphorus. Oxides of silicon. Formaldehyde. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|---|--|
| Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel. | |
| Environmental precautions: | Do not allow product to enter sewer or waterways. Remove all sources of ignition. |
| Clean-up methods: | Ensure adequate ventilation. Remove all sources of ignition. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. |

7. HANDLING AND STORAGE

| | |
|------------------|---|
| Handling: | Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. DO NOT heat or spray. Use only with adequate ventilation. Refer to Section 8. Use only in area provided with appropriate exhaust ventilation. |
| Storage: | For safe storage, store at or below 26 °C (78.8 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. |

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous components | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|----------------------|-----------|----------|-----------|--|
| Acrylate monomer | None | None | None | None |
| Urethane Polymer | None | None | None | None |
| Modified acrylamide | None | None | None | 0.1 mg/m ³ TWA (Skin) 0.025 ppm TWA (Skin) |
| Substituted silane | None | None | None | None |
| Photoinitiator | None | None | None | None |

Engineering controls:

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s). If this material is handled at elevated temperatures or under mist forming conditions, without engineering controls, a NIOSH approved respirator must be used.

Eye/face protection:

Safety goggles or safety glasses with side shields. Wear chemical goggles; face shield (if splashing is possible).

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Physical state: | Liquid |
| Color: | Pale yellow |
| Odor: | Mild |
| Odor threshold: | Not available |
| pH: | Not applicable |
| Vapor pressure: | < 5 mm Hg (68 °F (20°C)) |
| Boiling point/range: | > 200 °F (> 93.3 °C) |
| Melting point/ range: | Not available |
| Specific gravity: | 1.0945 |
| Vapor density: | > 1 |
| Flash point: | 73.9 °C (165.02 °F) Pinsky Martens closed cup |
| Flammable/Explosive limits - lower: | Not available |
| Flammable/Explosive limits - upper: | Not available |
| Autoignition temperature: | Not available |
| Evaporation rate: | Not available |
| Solubility in water: | Slight |
| Partition coefficient (n-octanol/water): | Not available |
| VOC content: | 0.72 %; 7.28 g/l (process) 0.87 %; 9.52 g/l (potential) 1.59 %; 17.40 g/l (total) (ASTM D5403) |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Stability: | Stable under normal conditions of storage and use. |
| Hazardous reactions: | May occur. |
| Hazardous decomposition products: | Oxides of carbon. Oxides of nitrogen. Oxides of phosphorus. Oxides of silicon. Formaldehyde. |
| Incompatible materials: | Strong oxidizing agents. Strong acids. Strong bases. Reducing agents. Peroxides. Free radical initiators. Other polymerization initiators. |
| Conditions to avoid: | Avoid temperatures above 26°C (80°F). Keep away from heat, spark and flame. Store away from incompatible materials. |

11. TOXICOLOGICAL INFORMATION

| | |
|---|--|
| Acute oral product toxicity: | Modified acrylamide LD50 (rat) 316 mg/kg |
| Acute dermal product toxicity: | Modified acrylamide LD50 (rabbit) 518 mg/kg |
| Acute inhalation product toxicity: | Modified acrylamide LC50 (rat) 1 h > 776 ppm (vapor) |

| Hazardous components | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|----------------------|----------------|-----------------|---|
| Acrylate monomer | No | No | No |
| Urethane Polymer | No | No | No |
| Modified acrylamide | No | No | No |
| Substituted silane | No | No | No |
| Photoinitiator | No | No | No |

| Hazardous components | Health Effects/Target Organs |
|----------------------|--|
| Acrylate monomer | Irritant, Allergen |
| Urethane Polymer | No Records |
| Modified acrylamide | Irritant, Eyes, Mutagen, Kidney, Less weight gain and food intake. |
| Substituted silane | Irritant, Allergen |
| Photoinitiator | No Records |

12. ECOLOGICAL INFORMATION

| | |
|--------------------------------|---------------|
| Ecological information: | Not available |
|--------------------------------|---------------|

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

| | |
|--|--|
| Recommended method of disposal: | Dispose of according to Federal, State and local governmental regulations. |
| Hazardous waste number: | Not a RCRA hazardous waste. |

14. TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

U.S. Department of Transportation Ground (49 CFR)

| | |
|----------------------------------|--|
| Proper shipping name: | Combustible liquid, n.o.s. (Modified Acrylamide) |
| Hazard class or division: | Combustible Liquid |
| Identification number: | NA 1993 |
| Packing group: | III |

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire
CERCLA/SARA 313: None above reporting de minimus
California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
WHMIS hazard class: B.3, D.1.B, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format. 1, 2, 3, 4, 5, 8, 9, 15

Prepared by: Jennifer Glieco, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.